

Product data sheet

Characteristics

VW3M5103R100

power cable - between servomotor BSH and servodrive - 4 x 4 mm² + 2 x 1 mm² -10m



Main

Product or Component Type	Power cable
Accessory / Separate Part Type	Preamsembled power cordset
Accessory / separate part category	Connection accessory
Product compatibility	Servo motor BMH, 1 7.48 in (190 mm))E EN 60204-1 Servo motor BMH, 3 8.07 in (205 mm))E EN 60204-1 Servo motor BSH, 2 5.51 in (140 mm)) Servo motor BSH, 3 5.51 in (140 mm)) Servo motor BSH, 4 5.51 in (140 mm))
Accessory / separate part destination	Between servo motor and servo drive
Range Compatibility	Lexium 15 Lexium 32 Lexium 05
Cable length	32.81 ft (10 m)
Cable composition	4 x 4 mm ² + 2 x 1 mm ²

Complementary

Electrical connection	Free end servo drive side Connector - industrial M40 servo motor side
Net Weight	9.11 lb(US) (4.13 kg)

Ordering and shipping details

Category	18263-LEXIUM 32 ACCESSORIES
Discount Schedule	PC51
GTIN	3389119207416
Nbr. of units in pkg.	1
Package weight(Lbs)	10.24 lb(US) (4.644 kg)
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.11 in (7.9 cm)
Package 1 width	17.17 in (43.6 cm)
Package 1 Length	17.60 in (44.7 cm)
Unit Type of Package 2	P06
Number of Units in Package 2	18
Package 2 Weight	215.09 lb(US) (97.564 kg)
Package 2 Height	28.94 in (73.5 cm)
Package 2 width	31.50 in (80 cm)
Package 2 Length	23.62 in (60 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------