

Eaton RM25030-2CHR

Catalog Number: RM25030-2CHR

Eaton Bussmann Series RM modular fuse block, Box lugs with hex screws, 30 A, 2P, 200 kA RMS symm, 120°C, 50 lb-inches max, Class R, CVR(I)-RH-25030, Black, 200 kAIC, 75 °C, DIN rail|Panel, 250 V, #2-14 AWG



General specifications

Product Name	Catalog Number
Eaton Bussmann Series RM modular fuse block	RM25030-2CHR
	UPC
	051712682909
Product Length/Depth	Product Height
3.2 in	2 in
Product Width	Product Weight
2 in	0.225625 lb
Warranty	Compliances
Not Applicable	RoHS Compliant
Certifications	
ARO	
European Pressure Equipment Directive (PED) 97 /23 EC	

Electrical rating

Amperage Rating

30 A

Impulse withstand voltage

200 kA RMS symmetrical

Interrupt rating

200 kAIC

Short-circuit rating

200 kA RMS symmetrical

Torque rating

50 lb-in maximum

Voltage rating

250 V

Physical details

Color

Black

Conductor material rated for

Both

Conductor temperature rating

75 °C

Conductor type

Stranded

Fuse type

Class R

Number of Poles

Two-pole

Operating temperature - max

120 °C

Operating temperature - min

120 °C

Wire size

#2-14 AWG

General information

Accessories

CVR(I)-RH-25030

Connection

Box lug

Mounting method

DIN rail

Panel

Special features

Box Lugs with Hex Screws

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

RM25030-2CHR-FUSE BLK R250V 30A 2P HX

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - RM25030-2CHR



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)