

XMLP040BD290

Electronic pressure sensors, Pressure sensors
XM, transmitter, XMLP, 40 bar, 7/16 female,
4...20 mA, M12, set of 1

Main

Range of Product	Telemecanique Pressure sensors XM
Product or Component Type	Electronic pressure sensors
Pressure sensor type	Pressure transmitter
Pressure sensor name	XMLP
Electrical circuit type	Control circuit
Pressure Rating	580.2 psi (40 bar)
Local display	Without
Controlled fluid	Fresh water 32...275 °F (0...135 °C)) Air -40...275 °F (-40...135 °C)) Hydraulic oil -40...275 °F (-40...135 °C)) Gas -40...275 °F (-40...135 °C)) Refrigeration fluid -40...275 °F (-40...135 °C))
Fluid connection type	SAE 7/16-20UNF-2B (female) with schrader
Electrical connection	1 male connector M12 4 pins
[Us] rated supply voltage	12...24 V DC SELV 7...33 V)
Current consumption	< 23 mA
Type of output signal	Analogue
Analogue output function	4...20 mA, 2-wire
Quantity per Set	Set of 1
Type of Packing	Individual

Complementary

Pressure setting range	0.000000000...580.2 psi (0...40 bar)
Maximum permissible accidental pressure	1740.5 psi (120 bar)
Destruction pressure	3480.9 psi (240 bar)
Materials in contact with fluid	Stainless steel type AISI 303
Operating position	Any position
Protection Type	Load short-circuit Reverse polarity
Electromagnetic compatibility	Electrostatic discharge immunity test IEC 61000-4-2 8 kV air, 4 kV contact 1.2/50 µs shock waves immunity test IEC 61000-4-5 1 kV 42 Ohm Immunity to magnetic fields IEC 61000-4-8 100 A/m 50 Hz Electrical fast transient/burst immunity test IEC 61000-4-4 4 kV Susceptibility to electromagnetic fields IEC 61000-4-3 10 V/m 80...3000 MHz Radiated RF fields IEC 61000-4-6 10 V 0.01...80 MHz
[Uimp] rated impulse withstand voltage	0.5 kV
Response time on output	<= 2 ms 10...90 % of full scale
Measurement accuracy	+/- 0.5 % of the measuring range
Resolution	0.1 % of the measuring range
Drift of the sensitivity	+/- 0.02 % of measuring range/°K
Drift of the zero point	+/- 0.02 % of measuring range/°K
Mechanical durability	10000000 cycles
Net Weight	0.2 lb(US) (0.1 kg)
Diameter	1.02 in (26 mm)
Length	1.7 in (44 mm)

Environment

Standards	NSF ANSI 61 IEC 61326-2-3
Product Certifications	CE[RETURN]cULus[RETURN]RCM
Protective treatment	TC
Ambient Air Temperature for Operation	-22...185 °F (-30...85 °C)
Ambient Air Temperature for Storage	-58...212 °F (-50...100 °C)
Vibration resistance	20 gn 15...2000 Hz) IEC 60068-2-6
Shock resistance	100 gn 11 ms IEC 60068-2-27
IP degree of protection	IP65 conforming to IEC 60529 IP67 conforming to IEC 60529 IP69K conforming to IEC 60529

Ordering and shipping details

Category	US10DS222419
Discount Schedule	0DS2
GTIN	3389119639255
Returnability	Yes
Country of origin	CH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.57 in (4.000 cm)
Package 1 Width	1.73 in (4.400 cm)
Package 1 Length	3.15 in (8.000 cm)
Package 1 Weight	3.527 oz (100.000 g)
Unit Type of Package 2	S01
Number of Units in Package 2	24
Package 2 Height	5.91 in (15 cm)
Package 2 Width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	5.961 lb(US) (2.704 kg)

Offer Sustainability

SCIP Number	63bf6aac-e7ba-4853-b69a-9632a64b72b3
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations