



Main

Device short name	MN delay unit
Product or Component Type	Time delay relay
Device Application	Control
Range compatibility	MasterPact NT MasterPact NW ComPact NS630b...1600 ComPact NS1600b...3200 MasterPact NW UL 489 MasterPact NT UL 489 MasterPact NW DC
Voltage release type	Undervoltage release
[Uc] control circuit voltage	380...480 V AC 50/60 Hz 380...480 V DC

Complementary

Impulse duration	200 ms
Time delay range	0.5...3 s
Threshold tripping voltage	0.35...0.7 Un open 0.85 Un close
Supply holding power	4.5 VA
Supply inrush power	200 VA
Mounting Mode	External mounting
Response time	0.5 s 1 s 1.5 s 3 s
Accessory / separate part category	Spare part Compact NS630b...1600 Spare part Compact NS1600b...3200

Ordering and shipping details

Category	01081-INTRA-COMPANY COMPONENTS
Discount Schedule	NET
GTIN	3303430336839
Nbr. of units in pkg.	1
Package weight(Lbs)	6.31 oz (179.0 g)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.35 in (8.5 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	3.54 in (9 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Weight	8.07 lb(US) (3.66 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------