



SKU: PDH-11-2/0-1

UPC: 0783669715996

Features & Benefits:

Description:Power Distribution Block, High SCCR, Dual Rated, Line Conductor Range 2/0-14, Load Range 2/0-14, 1 Port Per Pole Line Side, 1 Port Per Pole Load Side, 1 Pole, UL, CSA, Includes Cover

Specs

Additional Class Attributes

Block Size	NA
Connection	Mechanical
Mounting Hole Type	Thru
Mounting Method	Panel
Number of Conductors	2
Number of Mounting Holes	2
Number of Poles	1
Number of Ports Per Pole Primary	1
Number of Ports Per Pole Secondary	1

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range AL Stranded (Primary, run, main, line)	2/0 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	2/0 Str - 14 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	2/0 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol
High SCCR Conductor Range Line	2/0 Str - 6 Str
High SCCR Conductor Range Load	2/0 Str - 6 Str

Additional Technical Specifications

Connector Amperage Rating AL (Derated where applicable)	135 Amps
Connector Amperage Rating CU (Derated where applicable)	175 Amps
Conductor Type	Stranded
Fuse Required Class CC Amp Rating	30 Amps
Fuse Required Class GA Amp Rating	60 Amps
Fuse Required Class J Amp Rating	200 Amps
Fuse Required Class RK1 Amp Rating	200 Amps
Fuse Required Class RK5 Amp Rating	100 Amps
Fuse Required Class T Amp Rating	200 Amps

Dimensions

Drive Size Main	5/16
Drive Size Tap	5/16
Drive Type Main	Internal Hex
Drive Type Tap	Internal Hex
Height (IN)	0
Height BX (IN)	3.3125
Length (IN)	0
Mounting Bolt/Stud Size (mm)	254
Weight (LB)	0.1368
Width (IN)	0
Width BX (IN)	6.3125

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Enclosure Material	Thermoplastic
Insulation	NA
Material	Aluminum

Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10
Number of Wire Binding Screws per Port	1

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 12
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366971599

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
RUS Listed	No
UL Control Number	NA
UL / CULUS Specification	UL 1059 Recognized
UL File Number	E84782

Surge Specifications

Short Circuit Current Rating (SCCR)	100 kA
-------------------------------------	--------

Color

Color	Black
-------	-------

Voltage

Voltage Rating

600 V

Environment and Temperature

Flammability Rating

UL 94 V0

Temperature Rating

75°C