

Straight Blade Devices,
Receptacles, Duplex, Heavy Duty
Grade, 2-Pole 3-Wire Grounding,
20A 250V, 6-20R, Blue

By Hubbell Wiring Device-Kellems
Catalog # 5462BL

Straight Blade Devices, Receptacles, Duplex, Heavy Duty Grade,
2-Pole 3-Wire Grounding, 20A 250V, 6-20R, Blue

Features

- Back and side wired
- Fed- Spec UL listed
- Smooth nylon face, Brass triple-wipe contacts

Application

Hubbell-Pro Heavy Duty

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94 V-2
- Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact)
- Mechanical - Product Identification - Ratings are a permanent part of the device
- Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

General

Catalog Number	5462BL
Color	Blue
EU RoHS Indicator	Contact Manufacturer
Horsepower - Maximum	2
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Series	Hubbell-PRO
Style	Smooth Face
Type	Standard Duplex
UPC	783585555973



Dimensions

Weight	0.2 lb
--------	--------

Electrical Ratings

Amperage Rating	20 A
Connectivity	Back and Side Wired
Current / Amperage Rating	20 A
Current Rating	20 A
Dielectric Strength	Withstands 2,000V minimum
Voltage Rating Description	250 V
Wattage	5000 W

Conductor Related

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG

Certifications And Compliance

Industry Standard(s)	• Certified to CSA 22.2, No. 42 • Fed. Spec. W-C-596 • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186
Nema Rating	6-20R

Logistics

Carton Quantity	10
-----------------	----

Product Assets

[Catalog Page - WDK A-28 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)
[Engineering Drawing - 5462BL AutoCAD Drawing](#)
[Literature - Hubbell-PRO 15A & 20A 250V Duplex Receptacles](#)
[Specifications - 5462BL](#)
[Warranty - Industrial & Commercial Products](#)