

TELECOM MAIN GROUNDING BUSBAR, TINNED, 29"

CATALOG NUMBER

TMGBA29L41PT



CERTIFICATIONS



FEATURES

Meets TIA-607-C and TIA-607-D and conforms to BICSI® recommendations

Complies with NEMA® standards

Accepts two hole lugs with 5/16" or 7/16" bolt holes (hardware not included)

Telecom grounding busbar splice kits are available to extend the length of the busbar

PRODUCT ATTRIBUTES

Material: Copper

Tin Plating: Yes

Width (W): 4"

Thickness (T): 1/4"

Length 1 (L1): 29"

Length 2 (L2): 18"


Hole Size 1 (HS1): 5/16"

Hole Size 1 Number of Pairs: 41

Hole Size 2 (HS2): 7/16"

Hole Size 2 Number of Pairs: 5
A: 1"
B: 1 1/8"
C: 5/8"
D: 5/8"

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europe Netherlands: +31 800-0200135 France: +33 800 901 793	Europe Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--