

MODULAR TDX PANEL PROTECTOR, 400 KA, 120/208 V UN, 3PH 4W+G DISTRIBUTION SYSTEM

CATALOG NUMBER

TDX400S120/208



CERTIFICATIONS



FEATURES

Transient Discriminating (TD) Technology provides increased service life

Modular design allows easy replacement of surge modules

Built-in features include TD Technology, thermal protection, short circuit current cartridge fusing and a surge counter

Status indication flag per mode, voltage presence LEDs, audible alarm and voltage-free contacts providing remote status monitoring

400kA 8/20 μ s maximum surge rating provides protection suitable for service entrance, main-distribution panels and highly exposed applications

PRODUCT ATTRIBUTES

Nominal System Voltage (Un): 120/208 V

Distribution System: 3Ph 4W+G

Max Continuous Operating Voltage (Uc): 170/276 VAC

Stand-off Voltage: 240/415 VAC

Frequency: 50 - 60 Hz

Short Circuit Current Rating (SCCR): 200kA

Nominal Discharge Current (In), IEC: 40kA 8/20 μ s

Nominal Discharge Current (In), UL: 20kA 8/20 μ s

Max Discharge Current (Imax), Per Phase: 400kA 8/20 μ s

Impulse Current (Iimp), Per Mode: 25kA 10/350 μ s

Voltage Protection Rating (VPR), L-N: 800 V @ 3 kA

Protection Modes: L-N;L-PE;N-PE

Status Indication: LED;Mechanical flag;Audible alarm

Surge Counter: Yes

Technology: TD technology with thermal disconnect;Over-current replaceable cartridge fusing

Remote Contacts: Yes

Lead Length: 30"

Lead Size imperial: #10

Ground Lead Length: 36"

Temperature: -40 to 176 °F

Enclosure Material: Metal

Enclosure Rating: IP 20;NEMA®-12/3R

Mounting: 3/4" straight nipple

Depth (D): 3 1/4"

Height (H): 10.4"

Width (W): 10.32"


Unit Weight: 14 lb

Certification Details: UL® 1449 Edition 5 Type 1/2, 20 kA Mode

Complies With: ANSI®/IEEE® C62.41.2-2002 Scenario II, Exposure 3, 100 kA 8/20 μ s, 10 kA 10/350 μ s;IEC® 61643-1 Class I, Class II

Replacement Module: TDS150M150

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation,

misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER