

GROUND ROD CLAMP, U-BOLT, THREE CONDUCTORS, 5/8"–3/4" DIA, 2/0 SOLID-250 KCMIL STRANDED, 70 MM² STRANDED-120 MM² STRANDED

CATALOG NUMBER

GC065TH



FEATURES

Ground rod clamp that allows up to three separate conductors to be connected to a ground rod

Bronze material is a copper alloy with high copper content

Tinned bronze has theft-deterrent appearance

PRODUCT ATTRIBUTES

Material: Bronze


Finish: Tinned

Ground Rod Diameter, Nominal: 5/8" - 3/4"

Ground Rod Diameter, Actual (Ø): 0.620" - 0.75"

Conductor Size: 2/0 Solid - 250 kcmil Stranded; 70 mm² Stranded - 120 mm² Stranded

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

⚠ **WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

North America	Europe	Europe	APAC
+1.800.753.9221	Netherlands:	Germany:	Shanghai:
Option 1 – Customer Care	+31 800-0200135	800 1890272	+ 86 21 2412 1618/19
Option 2 – Technical Support	France:	Other Countries:	Sydney:
	+33 800 901 793	+31 13 5835404	+61 2 9751 8500