


NON-INSULATED STRANDED CONDUCTOR FOR LIGHTNING PROTECTION, COPPER, SMOOTH WEAVE, 73.8 KCMIL

CATALOG NUMBER

LPC123CTO



CERTIFICATIONS



FEATURES

Provides a path to ground for lightning currents

PRODUCT ATTRIBUTES

Certification Details: UL® 96

Material: Copper

UL Conductor Class: Class I

Conductor Type: Smooth Weave

Number of Wires: 36

Wire Diameter: 0.04"

Diameter: 0.45"

Cross Section: 73.8

Unit Weight: 0.24 lb

ADDITIONAL PRODUCT DETAILS

Unit weight is per foot (0.3048 m).
Cut-to-order (CTO) lengths are available for an additional charge.

Equivalent Conductor Size	
Part Number	Conductor Size
LPC134xxx	2/0
LPC136xxx	3/0
LPC137xxx	4/0

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europe Netherlands: +31 800-0200135 France: +33 800 901 793	Europe Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--