





Main

Range	TeSys
Product name	TeSys island
Device short name	TPRSS
Product or Component Type	SIL motor starter
Motor starter type	Direct on line
Device presentation	Direct starter connected to an automation controller through a bus coupler Operational only when connected to a bus coupler
Function Available	Upstream voltage presence detection Electrical line and load protection Power and energy monitoring when connected with TPRVM voltage module Safe stop function available when connected with a TPRSM module
Product compatibility	TPRBC bus coupler TPRVM voltage interface module TPRSM SIL interface module
Poles description	3P 3 NO
Utilisation category	AC-1 AC-2 AC-3 AC-4
Motor power kW	9 kW 230 V 50 Hz AC-3) 18.5 kW 380...415 V 50 Hz AC-3) 18.5 kW 440 V 50 Hz AC-3) 18.5 kW 500 V 50 Hz AC-3) 18.5 kW 690 V 50 Hz AC-3)
Motor power HP (UL / CSA)	2 Hp 120 V at AC 60 Hz for 1 phase 5 Hp 240 V at AC 60 Hz for 1 phase 10 Hp 208 V at AC 60 Hz for 3 phase 10 Hp 240 V at AC 60 Hz for 3 phase 20 Hp 480 V at AC 60 Hz for 3 phase 25 hp 600 V at AC 60 Hz for 3 phase
[Ue] rated operational voltage	<= 480 V AC 47...63 Hz for overvoltage cat. III <= 690 V AC 47...63 Hz for overvoltage cat. II
[Ie] rated operational current	38 A 122 °F (50 °C)) <= 440 V AC-3 40 A 122 °F (50 °C)) <= 440 V AC-1
[Ith] conventional free air thermal current	40 A 122 °F (50 °C)
[Ui] rated insulation voltage	690 V IEC 60947-4-1 600 V UL 60947-4-1 600 V CSA C22.2 No 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-1
Overvoltage category	III for Ue <= 480 V II for Ue <= 690 V
Thermal protection adjustment range	0.76...38 A
Thermal overload class	Class 5...30
Reset	Remotely or automatically
Irms rated making capacity	550 A 440 V IEC 60947
Rated breaking capacity	550 A 440 V IEC 60947
[Icw] rated short-time withstand current	430 A 104 °F (40 °C) - 1 s 310 A 104 °F (40 °C) - 10 s 150 A 104 °F (40 °C) - 1 min 60 A 104 °F (40 °C) - 10 min
Average impedance	2 mOhm - Ith 40 A 50 Hz
Power dissipation per pole	2.9 W AC-3 - Ith 38 A 3.2 W AC-1 - Ith 40 A
[Uc] control circuit voltage	24 V DC supplied by the bus coupler

Current consumption	160 mA contactor sealed 160 mA contactor closing
Power dissipation in W	11.8 W at le AC-3

Complementary

Mechanical durability	30 Mcycles
Electrical durability	1.4 Mcycles 38 A AC-3 440 V 2 Mcycles 40 A AC-1 440 V
Maximum operating rate	3600 cyc/mn AC-3
Operating time	< 100 ms closing < 30 ms opening
Safety function	Safe stop: category 0 conforming to IEC 60204-1 when associated with a TPRSM module Safe stop: category 1 conforming to IEC 60204-1 when associated with a TPRSM module
Safety integrity level	SIL 2 conforming to IEC 61508 in single channel system architecture SILCL 2 conforming to IEC 62061 in single channel system architecture PL = d category 2 conforming to ISO 13849-1 in single channel system architecture
Safety performance level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Protection type	Thermal overload protection Motor overload Overcurrent Undercurrent Jam Long start Stall Rapid cycle lockout Rapid restart lockout Phase sequence Phase reversal Phase loss Phase unbalance Ground current
Monitoring type	Time device ON Time device switch ON Number of faults Number of switching cycles Number of device power cycles Average current Iavg Average voltage Vavg Max current Imax Max voltage Vmax Active and reactive power with voltage module Active and reactive energy with voltage module True power factor with voltage module
Local signalling	For DS (device status) 1 LED (green/red) For LS (load status) 1 LED (green/red)
Standards	EN/IEC 60947-1 EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product certifications	CSA[RETURN]EAC[RETURN]UL[RETURN]CCC
Mounting mode	Horizontal and vertical 35 mm symmetrical DIN rail)
Connections - terminals	Screw-clamp terminals 1 0.00...0.02 in ² (1.5...10 mm ²) AWG 16...AWG 8)rigid Screw-clamp terminals 2 0.00...0.02 in ² (1.5...10 mm ²) AWG 16...AWG 8)rigid Screw-clamp terminals 1 0.00...0.02 in ² (2.5...10 mm ²) AWG 14...AWG 8)flexible without cable end Screw-clamp terminals 2 0.00...0.02 in ² (2.5...10 mm ²) AWG 14...AWG 8)flexible without cable end Screw-clamp terminals 1 0.00...0.02 in ² (1.5...10 mm ²) AWG 16...AWG 10)flexible with cable end Screw-clamp terminals 2 0.00...0.01 in ² (1.5...6 mm ²) AWG 16...AWG 10)flexible with cable end
Tightening torque	22.13 Lbf.in (2.5 N.m) flat Ø 6 mm 22.13 lbf.in (2.5 N.m) Philips No 3
Width	1.77 in (45 mm)
Height	4.76 in (121 mm)
Depth	4.53 in (115 mm)
Net Weight	1.58 lb(US) (0.718 kg)

Environment

Ambient air temperature for storage	-13...158 °F (-25...70 °C)
Ambient air temperature for operation	14...122 °F (-10...50 °C) without derating 122...140 °F (50...60 °C) with current derating
Relative Humidity	5...95 %
Operating altitude	0...6561.68 ft (0...2000 m) without derating
IP degree of protection	IP20
Pollution degree	2
Protective treatment	TC
Fire resistance	1760 °F (960 °C) UL 94 1562 °F (850 °C) IEC 60695-2-1 1202 °F (650 °C) IEC 60695-2-12
Shock resistance	15 gn 11 ms) IEC 60068-2-27
Vibration resistance	1.5 mm peak to peak 3...13 Hz) IEC 60068-2-6 1 gn 13...200 Hz) IEC 60068-2-6
Electromagnetic compatibility	Electrostatic discharge immunity test, level 3, 8 kV air, 6 kV contact, conforming to EN/IEC 61000-4-2 Radiated RF field immunity test, level 3, 10 V/m, conforming to EN/IEC 61000-4-3 Fast transient immunity test, level 4, 4 kV, conforming to EN/IEC 61000-4-4 Surge immunity test (differential mode), level 3, 2 kV, conforming to EN/IEC 61000-4-5 Surge immunity test (common mode), level 4, 4 kV, conforming to EN/IEC 61000-4-5 Conducted RF disturbance immunity test, 20 V, conforming to EN/IEC 61000-4-6

Ordering and shipping details

Category	22352-TESYS ISLAND LOAD CONTROLLERS
Discount Schedule	I12
GTIN	3606489832810
Returnability	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.17 in (5.5 cm)
Package 1 Width	4.92 in (12.5 cm)
Package 1 Length	5.12 in (13 cm)
Package 1 Weight	27.23 oz (772 g)
Unit Type of Package 2	S02
Number of Units in Package 2	14
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	24.49 lb(US) (11.109 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------