

GV4ADM1111

Motor circuit breaker, TeSys Deca, 2 normally open and 2 normally closed contacts, SDx contact module, GV4PEM



Main

Range	TeSys
Device short name	GV4A
Product or Component Type	Auxiliary contact block
Device application	Signalling
Range compatibility	TeSys GV4 multifunction circuit breaker
Mounting Location	Right side
Mounting Mode	Clipped
Pole contact composition	2 NO + 2 NC

Complementary

[Ui] rated insulation voltage	250 V IEC 60947-1
[Ue] rated operational voltage	24...250 V AC 24...250 V DC
[Ith] conventional free air thermal current	5 A
Associated fuse rating	5 A gG IEC 60947-5-1
Mechanical durability	100000 cycles
Minimum switching current	2 mA
Minimum switching voltage	17 V
Rated operational power in VA	400 VA 230...240 V AC-12
Rated operational power in W	50 W 24 V DC-12

Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

Ordering and shipping details

Category	22366-MAN STR PROTECTORS-GV1/GV3
Discount Schedule	I11
GTIN	3606481166753
Nbr. of units in pkg.	1
Package weight(Lbs)	5.29 oz (150 g)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.18 in (3 cm)
Package 1 width	3.54 in (9 cm)
Package 1 Length	6.14 in (15.6 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	18
Package 2 Weight	6.61 lb(US) (3 kg)
Package 2 Height	5.91 in (15 cm)

Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.