



Main

Accessory / separate part category	Connection accessories
Accessory / separate part type	Connecting cable
Accessory / separate part designation	AS-Interface flat cable
Accessory / separate part destination	AS-Interface cabling system
Cable length	65.62 ft (20 m)
Wire insulation material	Rubber
Color	Yellow

Complementary

Clamping Connection Capacity	2 x 1.5 mm ²
[Ue] rated operational voltage	<= 48 V
Net Weight	3.09 lb(US) (1.4 kg)

Environment

IP Degree of Protection	IP67
Ambient Air Temperature for Operation	77...185 °F (25...85 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

Ordering and shipping details

Category	18325-SERIPLEX SOFTWARE&CABLES DISC SPX2
Discount Schedule	SPX2
GTIN	3389110610550
Nbr. of units in pkg.	1
Package weight(Lbs)	3.60 lb(US) (1.635 kg)
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.71 in (14.5 cm)
Package 1 width	7.68 in (19.5 cm)
Package 1 Length	8.27 in (21 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	4
Package 2 Weight	15.69 lb(US) (7.118 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------