

PNOZ XV3 0.5/24VDC 3n/o 2n/o t fix

774544



Safety relay (standalone), inputs: 1/2-channel wiring with/without detection of shorts across contacts, outputs: 3 N/O, 2 N/Ot-d, UB = 24 V DC, width: 45 mm, screw terminals integrated, E-STOP monitoring, safety gates with 2 delay-on de-energisation contacts, release time 0.5s fixed.

Technical details

General data

Approval: CCC, CE, UKCA, cULus Listed, EAC (Eurasian), TÜV

Technical data

Environment

RoHS directive: 2011/65/EU, 2015/863/EU

RoHS conformity: 0

RoHS exceptions: 0

RoHS except.s acc. to direct.: 7A, 7C I

REACH compliance: 1

REACH included substances: Blei, Bleioxid

%-part of the pollutant: > 0,1

CAS No.: 7439-92-1, 1317-36-8

SCIP entry available: yes

WEEE classification (08/2018): U_KATEGORIE_5

Commercial data

ECLASS version: ECLASS-13

ECLASS Reference Feature: 27371819

ETIM Version: ETIM-9.0

ETIM Reference Group: EG000019

ETIM Reference Feature: EC001449

UNSPSC 25:	39122331
GTIN:	4046548010992
Volume:	0.563
Harmonized System Code:	85364900
Type of tariff number:	TARIC
Use of customs tariff number:	export, Import
Quantity per packaging unit:	1

Optional accessories

774090

COVER P-93

