

# BJL 16020

Circuit breaker, PowerPact B, 20A, 1 pole,  
600Y/347VAC, 25kA, lugs, thermal magnetic,  
80%



## Main

|                           |                 |
|---------------------------|-----------------|
| Range                     | PowerPact       |
| Product name              | PowerPact B     |
| Device short name         | BJ 020          |
| Product or Component Type | Circuit breaker |
| Device Application        | Distribution    |

## Complementary

|                                        |                                                                                                                                                                                                |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Line Rated Current                     | 20 A                                                                                                                                                                                           |
| Number of Poles                        | 1P                                                                                                                                                                                             |
| Protected poles description            | 1t                                                                                                                                                                                             |
| Control Type                           | Toggle                                                                                                                                                                                         |
| Breaking capacity code                 | J                                                                                                                                                                                              |
| Breaking capacity                      | 100 KA 208Y/120 V AC 50/60 Hz UL 489<br>100 KA 240 V AC 50/60 Hz UL 489<br>65 KA 480Y/277 V AC 50/60 Hz UL 489<br>25 KA 600Y/347 V AC 50/60 Hz UL 489<br>50 kA 125 V DC UL 489                 |
| [Ue] rated operational voltage         | 240 V AC 50/60 Hz UL 489                                                                                                                                                                       |
| Network Frequency                      | 50/60 Hz                                                                                                                                                                                       |
| [Ics] rated service breaking capacity  | 65 kA 220...240 V AC 50/60 Hz IEC 60947-2                                                                                                                                                      |
| [Uimp] rated impulse withstand voltage | 8 kV IEC 60947-2                                                                                                                                                                               |
| Trip unit technology                   | Thermal-magneticTM-D,                                                                                                                                                                          |
| Continuous current rating              | 80 %                                                                                                                                                                                           |
| [Ui] rated insulation voltage          | 800 V IEC 60947-2                                                                                                                                                                              |
| Trip unit name                         | TM-D                                                                                                                                                                                           |
| Suitability for isolation              | Yes IEC 60947-2                                                                                                                                                                                |
| Utilisation category                   | Category A                                                                                                                                                                                     |
| Mechanical durability                  | 15000 cycles IEC 947-1 Annex F ed 5.2                                                                                                                                                          |
| Electrical durability                  | 10000 cycles IEC 947-1 Annex K ed 5.2 In                                                                                                                                                       |
| Connection pitch                       | 1.06 in (27 mm)                                                                                                                                                                                |
| AWG gauge                              | AWG 6...AWG 2/0 fine stranded aluminium/copper<br>AWG 14...AWG 3/0 rigid or stranded aluminium/copper                                                                                          |
| Mounting mode                          | Clip-on 35 mm symmetrical DIN rail)<br>By screws plate)                                                                                                                                        |
| Electrical connection                  | Everlink lug line<br>Everlink lug load                                                                                                                                                         |
| Tightening torque                      | 44.25 Lbf.in (5 N.m) 0.00...0.02 in <sup>2</sup> (2.5...16 mm <sup>2</sup> ) (AWG 14...AWG 4)<br>79.66 lbf.in (9 N.m) 0.04...0.15 in <sup>2</sup> (25...95 mm <sup>2</sup> ) (AWG 3...AWG 3/0) |
| Power wire stripping length            | 0.79 in (20 mm)                                                                                                                                                                                |
| Color                                  | Gray RAL 7016)                                                                                                                                                                                 |
| 9 mm pitches                           | 3                                                                                                                                                                                              |
| Height                                 | 5.39 in (137 mm)                                                                                                                                                                               |
| Width                                  | 1.06 in (27 mm)                                                                                                                                                                                |

|                  |                       |
|------------------|-----------------------|
| Depth            | 3.15 in (80 mm)       |
| Net Weight       | 1.12 lb(US) (0.51 kg) |
| Quantity per Set | Set of 1              |

## Environment

|                                       |                                                                                                       |
|---------------------------------------|-------------------------------------------------------------------------------------------------------|
| Quality labels                        | CE                                                                                                    |
| Standards                             | UL 489<br>EN/IEC 60947-2<br>NMX J-266<br>CSA C22.2 No 5<br>EN/IEC 60947-5-1<br>NEMA AB1<br>GB 14048.2 |
| Product certifications                | UL<br>IEC<br>CCC<br>EAC<br>CSA<br>NOM                                                                 |
| IP degree of protection               | Front cover IP40 IEC 60529                                                                            |
| IK degree of protection               | IK07 IEC 62262                                                                                        |
| Pollution degree                      | 3 IEC 60947-1                                                                                         |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C)                                                                            |
| Ambient Air Temperature for Storage   | -58...185 °F (-50...85 °C)                                                                            |
| Operating altitude                    | 6561.68 ft (2000 m) without derating<br>5000 m with derating                                          |

## Ordering and shipping details

|                       |                                       |
|-----------------------|---------------------------------------|
| Category              | 01132-BJ/BK UNIT MOUNT BREAKER/SWITCH |
| Discount Schedule     | DE2                                   |
| GTIN                  | 3606481193896                         |
| Nbr. of units in pkg. | 1                                     |
| Package weight(Lbs)   | 16.00 oz (453.592 g)                  |
| Returnability         | Yes                                   |
| Country of origin     | MX                                    |

## Packing Units

|                        |                     |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE                 |
| Package 1 Height       | 1.40 in (3.556 cm)  |
| Package 1 width        | 4.70 in (11.938 cm) |
| Package 1 Length       | 7.50 in (19.05 cm)  |

## Offer Sustainability

|                             |                                                                                                                                                                                                                                                                                                                                    |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status    | Green Premium product                                                                                                                                                                                                                                                                                                              |
| California proposition 65   | WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation            | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                                                                  |
| EU RoHS Directive           | Compliant <a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                                                                                                      |
| Mercury free                | Yes                                                                                                                                                                                                                                                                                                                                |
| RoHS exemption information  | <a href="#">Yes</a>                                                                                                                                                                                                                                                                                                                |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>                                                                                                                                                                                                                                                                                             |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                                                                                      |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.                                                                                                                                                                                                       |
| PVC free                    | Yes                                                                                                                                                                                                                                                                                                                                |
| Halogen content performance | Halogen free product                                                                                                                                                                                                                                                                                                               |