

Kellems Wire Management, Cord
Connectors, European Style
.25-.48", 3/4", Gray

By Hubbell Wiring Device-Kellems
Catalog # [SEC75RGA](#)

Kellems Wire Management, Cord Connectors, European Style
.25-.48", 3/4", Gray

Application

Straight Male

Performance

Flammability - UL 94X-2

General

Catalog Number	SEC75RGA
Color	Gray
EU RoHS Indicator	No
Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Nylon Washer Between Box And Fitting.
Item Type	Low Profile NPT Cord Connectors
Material	Nylon
Material - Mounting Hardware	Locknut or Tapped Opening
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	-22 Deg F to 225 Deg F (-30 Deg C to 107 Deg C)
Temperature Rating	Minimum -22°F to 225°F (-30°C to 107°C).
Type	Low Profile NPT Cord Connectors
UPC	783585346915

Dimensions



Display Size	3/4" NPT
Conductor Related	
Conductor Range	0.25-0.48 in (6.35-12.19 mm)
Number of Conductors	Single
Certifications And Compliance	
Industry Standard(s)	UL Listing File E-41567, UL Recognition File E-41567;CSA File LR27378C, VDE Marks Licence #136681
Nema Rating	IP66
Logistics	
Carton Quantity	50
Product Assets	
Catalog Page - WDK W-74 Catalog Page - WDK W-73 Catalogs - WDK Catalog Full 2024	
Literature - Wire Management Solutions Brochure	
Literature - FOOD & BEVERAGE SOLUTIONS	
Literature - PULP & PAPER SOLUTIONS	
Literature - Pulp & Paper Solutions	
Literature - FOOD & BEVERAGE SOLUTIONS	
Specifications - SEC75RGA	
Warranty - Industrial & Commercial Products	
Video - Kellems Wire Management Solutions	