

Eaton 277261

Catalog Number: 277261

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 15 kW, 1 N/O, 380 V 50 Hz, 440 V 60 Hz, AC operation, Screw terminals



General specifications

Product Name	Catalog Number
Eaton Moeller® series DILM contactor	277261
Model Code	EAN
DILM32-10(380V50HZ,440V60HZ)	4015082772611
Product Length/Depth	Product Height
97 mm	85 mm
Product Width	Product Weight
45 mm	0.428 kg
Certifications	Catalog Notes
CSA IEC/EN 60947 VDE 0660 UL	Contacts according to EN 50012

Product specifications

Terminal capacity (flexible with ferrule)

2 x (0.75 - 10) mm², Main cables

1 x (0.75 - 16) mm², Main cables

1 x (0.75 - 2.5) mm², Control circuit cables

2 x (0.75 - 2.5) mm², Control circuit cables

Rated operational current for specified heat dissipation (In)

32 A

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Rated operational power at AC-3, 380/400 V, 50 Hz

15 kW

Conventional thermal current Ith (3-pole, enclosed)

36 A

Rated operational power at AC-4, 380/400 V, 50 Hz

7 kW

Rated operational current (Ie) at AC-4, 440 V

15 A

Rated control supply voltage (Us) at AC, 50 Hz - min

380 V

Conventional thermal current Ith at 60°C (3-pole, open)

40 A

10.4 Clearances and creepage distances

Meets the product standard's requirements.

Number of contacts (normally closed) as main contact

0

Conventional thermal current Ith at 55°C (3-pole, open)

42 A

Rated operational power (NEMA)

14.9 kW

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Ambient storage temperature - min

40 °C

Rated breaking capacity at 380/400 V

320 A

Resources

Catalogs

[Product Range Catalog Switching and protecting motors](#)

[Switching and protecting motors - catalog](#)

[SmartWire-DT Catalog](#)

Characteristic curve

[eaton-contactors-component-dilm-characteristic-curve-003.eps](#)

[eaton-contactors-switch-dilm-characteristic-curve.eps](#)

[eaton-contactors-switch-dilm-characteristic-curve-002.eps](#)

Declarations of conformity

[DA-DC-00004783.pdf](#)

[DA-DC-00004816.pdf](#)

Drawings

[eaton-contactors-dilm-dimensions.eps](#)

[eaton-contactors-mounting-dilm-dimensions.eps](#)

[eaton-contactors-mounting-dilm-dimensions-002.eps](#)

[eaton-contactors-contact-dilm-dimensions-002.eps](#)

[eaton-contactors-dilm-3d-drawing-009.eps](#)

[eaton-general-ie-ready-dilm-contactor-standards.eps](#)

eCAD model

[DA-CE-ETN.DILM32-10\(380V50HZ,440V60HZ\)](#)

Installation instructions

[IL03407014Z](#)

Installation videos

[WIN-WIN with push-in technology](#)

mCAD model

[DA-CD-dil_m17_38](#)

[DA-CS-dil_m17_38](#)

System overview

[eaton-contactors-dilm-contactor-system-overview.eps](#)

Wiring diagrams

[eaton-contactors-contact-dilm-wiring-diagram.eps](#)

Rated control supply voltage (Us) at AC, 50 Hz - max

380 V

Rated breaking capacity at 660/690 V

180 A

Rated operational current (Ie) at DC-1, 220 V

40 A

Ambient operating temperature - max

60 °C

Rated operational power at AC-4, 440 V, 50 Hz

8 kW

Electrical connection type of main circuit

Screw connection

Number Of Poles

Three-pole

Ambient operating temperature - min

-25 °C

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

Application

Contactors for Motors

Operating frequency

5000 mechanical Operations/h (AC operated)

Voltage type

AC

Short-circuit protection rating (type 1 coordination) at 400 V

125 A gG/gL

Product category

Contactors

Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V

15 A

Rated operational power at AC-3, 690 V, 50 Hz

17 kW

Power consumption, pick-up, 50 Hz

52 VA, Dual-frequency coil in a cold state and $1.0 \times U_s$, at 50 Hz

Heat dissipation capacity P_{diss}

0 W

Switching time (AC operated, make contacts, opening delay) - min

8 ms

Rated operational current (I_e) at AC-4, 500 V

15 A

Rated operational power at AC-3, 240 V, 50 Hz

11 kW

Operating voltage at AC, 60 Hz - max

690 V

Terminal capacity (solid/stranded AWG)

18 - 14, Control circuit cables

Single 18 - 6, double 18 - 8, Main cables

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

Degree of protection

IP00

Overvoltage category

III

Switching time (AC operated, make contacts, opening delay) - max

14 ms

Ambient storage temperature - max

80 °C

Pollution degree

3

Rated operational current (I_e) at AC-1, 380 V, 400 V, 415 V

45 A

Power consumption, pick-up, 60 Hz

67 VA, Dual-frequency coil in a cold state and $1.0 \times U_s$, at 60 Hz

Switching time (AC operated, make contacts, closing delay) - max

22 ms

Rated impulse withstand voltage (Uimp)

8000 V AC

Connection

Screw terminals

Operating voltage at AC, 60 Hz - min

24 V

Tightening torque

3.2 Nm, Screw terminals, Main cables

1.2 Nm, Screw terminals, Control circuit cables

Rated operational power at AC-4, 660/690 V, 50 Hz

10 kW

Frame size

FS2

Conventional thermal current I_{th} (1-pole, enclosed)

90 A

Rated operational current (I_e) at AC-3, 660 V, 690 V

18 A

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.7 Inscriptions

Meets the product standard's requirements.

Rated operational current (I_e) at AC-3, 380 V, 400 V, 415 V

32 A

Number of contacts (normally open contacts)

1

Switching time (AC operated, make contacts, closing delay) - min

16 ms

Short-circuit protection rating (type 2 coordination) at 400 V

63 A gG/gL

Number of auxiliary contacts (normally open contacts)

1

Rated operational power at AC-3, 500 V, 50 Hz

23 kW

Shock resistance

10 g, N/O main contact, Mechanical, according to IEC/EN

60068-2-27, Half-sinusoidal shock 10 ms

3.5 g, N/C auxiliary contact, Mechanical, according to IEC/EN

60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN

60068-2-27, Half-sinusoidal shock 10 ms

6.9 g, N/O main contact, Mechanical, according to IEC/EN

60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

5.3 g, N/O auxiliary contact, Mechanical, according to IEC/EN

60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Mechanical, according to IEC/EN

60068-2-27, Half-sinusoidal shock 10 ms

Rated operational current (I_e) at DC-1, 110 V

40 A

Drop-out voltage

AC operated: 0.6 - 0.3 x UC, AC operated

Power consumption, sealing, 60 Hz

8.7 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

2.1 W, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

Resistance per pole

2.7 m Ω

Ambient operating temperature (enclosed) - min

25 °C

Stripping length (control circuit cable)

10 mm

Operating voltage at AC, 50 Hz - max

690 V

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

Stripping length (main cable)

10 mm

Ambient operating temperature (enclosed) - max

40 °C

Rated control supply voltage (Us) at DC - min

0 V

10.8 Connections for external conductors

Is the panel builder's responsibility.

Number of main contacts (normally open contact)

3

Rated breaking capacity at 220/230 V

320 A

Screw size

M5, Terminal screw, Main cables

M3.5, Terminal screw, Control circuit cables

Rated operational current (Ie) at AC-4, 400 V

15 A

Short-circuit protection rating (type 2 coordination) at 690 V

35 A gG/gL

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Power consumption, sealing, 50 Hz

2.1 W, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

7.1 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

Rated operational power at AC-3, 440 V, 50 Hz

20 kW

Terminal capacity (stranded)

1 x 16 mm², Main cables

Rated breaking capacity at 500 V

320 A

Rated operational power at AC-3, 415 V, 50 Hz

19 kW

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Emitted interference

According to EN 60947-1

Connection to SmartWire-DT

No

Static heat dissipation, non-current-dependent Pvs

2.1 W

Rated control supply voltage (Us) at DC - max

0 V

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

Utilization category

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

Rated operational current (I_e) at AC-3, 440 V

32 A

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

Safe isolation

440 V AC, Between coil and contacts, According to EN 61140

440 V AC, Between the contacts, According to EN 61140

Operating voltage at AC, 50 Hz - min

24 V

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Heat dissipation per pole, current-dependent P_{vid}

2.2 W

Actuating voltage

380 V 50 Hz, 440 V 60 Hz

Rated operational current (I_e) at AC-4, 660 V, 690 V

12 A

Equipment heat dissipation, current-dependent P_{vid}

6.6 W

Pick-up voltage

0.8 - 1.1 V AC x U_c

Suitable for

Also motors with efficiency class IE3

Conventional thermal current I_{th} at 40°C (3-pole, open)

45 A

Terminal capacity (solid)

1 x (0.75 - 4) mm², Control circuit cables
2 x (0.75 - 2.5) mm², Control circuit cables
1 x (0.75 - 16) mm², Main cables
2 x (0.75 - 10) mm², Main cables

Number of auxiliary contacts (normally closed contacts)

0

Interference immunity

According to EN 60947-1

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

Lifespan, mechanical

10,000,000 Operations (AC operated)

Short-circuit protection rating (type 1 coordination) at 690 V

63 A gG/gL

Rated making capacity up to 690 V (cos phi to IEC/EN 60947)

384 A

Rated operational power at AC-4, 240 V, 50 Hz

4.5 kW

Rated operational power at AC-4, 500 V, 50 Hz

9 kW

Rated operational current (Ie) at DC-1, 60 V

40 A

Rated operational power at AC-4, 220/230 V, 50 Hz

4 kW

Rated operational voltage (Ue) at AC - max

690 V

Rated control supply voltage (Us) at AC, 60 Hz - min

440 V

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

Conventional thermal current I_{th} at 50°C (3-pole, open)

43 A

Rated operational current (I_e) at AC-3, 500 V

32 A

Screwdriver size

2, Terminal screw, Pozidriv screwdriver

0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver

Duty factor

100 %

Rated operational current (I_e) at AC-3, 220 V, 230 V, 240 V

32 A

Conventional thermal current I_{th} of main contacts (1-pole, open)

100 A

Rated control supply voltage (U_s) at AC, 60 Hz - max

440 V

Arcing time

10 ms

Rated operational power at AC-4, 415 V, 50 Hz

7.5 kW

Rated insulation voltage (U_i)

690 V

Altitude

Max. 2000 m