



Main

Range	Thalassa
Product name	Thalassa PLM
Device short name	PLM
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	29.41 in (747 mm)
Nominal width	21.10 in (536 mm)
Nominal depth	11.81 in (300 mm)
Enclosure mounting	Wall mounted
Device composition	1 body 1 door 1 mounting plate 2 lock
Door type	Solid
Lock type	3 mm double-bar lock

Complementary

Number of locks	2
Mounting plate description	Plain bakelite
Accessibility for operation	Front
Removable parts	Door by hinges Mounting plate by fixing element
Material	Polyester reinforced with fibreglass
Color	Gray RAL 7035)
Standards	NEMA classification 13 IEC 62208 NEMA classification 4X
Product certifications	UL
Electrical insulation class	Class II

Environment

IP degree of protection	IP66 IEC 60529
IK degree of protection	IK10 IEC 62262
Fire resistance	1760 °F (960 °C) IEC 62208
Ambient Air Temperature for Operation	-40...176 °F (-40...80 °C)

Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480776700
Nbr. of units in pkg.	1
Package weight(Lbs)	35.71 lb(US) (16.2 kg)
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	22.05 in (56 cm)
Package 1 width	12.99 in (33 cm)
Package 1 Length	30.71 in (78 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	1
Package 2 Weight	35.71 lb(US) (16.2 kg)
Package 2 Height	12.99 in (33 cm)
Package 2 width	22.05 in (56 cm)
Package 2 Length	31.89 in (81 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile