

Main

Range	PowerLogic
Product name	PowerLogic HDPM6000
Product or Component Type	Power supply

Complementary

Power Consumption in VA	211.3 VA
Kw Rating	90 W
Supply voltage limits	264...575 V AC
Network frequency	50 Hz +/- 10 % 60 Hz +/- 10 %
Primary voltage	480 V 0.48 A AC
Secondary voltage	24 V DC
Associated fuse rating	2 A
Inrush current	30 A
Maximum output current	3.75 A
Width	2.17 in (55 mm)
Height	3.54 in (90 mm)
Depth	3.31 in (84 mm)
Net Weight	0.71 lb(US) (0.32 kg)

Environment

IP degree of protection	IP20
Relative humidity	0...95 % without condensation
Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

Ordering and shipping details

Category	09764-TRENDPOINT
Discount Schedule	PL1
GTIN	3606481985927
Nbr. of units in pkg.	1
Package weight(Lbs)	17.64 oz (500 g)
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.76 in (7 cm)
Package 1 width	4.02 in (10.2 cm)
Package 1 Length	4.49 in (11.4 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration