

Product data sheet

Specifications



Unit Substation, Mini Power-Zone,
3 Phase, 30kVA, 480V Pri,
208Y120 Sec, Type 3R, 18kA, wall
mounted, bolt on branch

MPUB30T2F

Product availability: Non-Stock - Not normally stocked in
distribution facility

Main

Certifications	UL Listed
Type	Mini Power-Zone
Phase	3 phase
Primary Voltage	480 V
Secondary Voltage	208Y/120 V
Full Capacity Taps	2 5 % FCBN
Power Rating	30 kVA
Temperature Rise	115 °C
Winding Material	Copper
Interrupt Rating	18 kA
Interior Type	NQ Panelboard interior
Number of Spaces Available	27.0
Number of Circuits	27.0
Enclosure Type	NEMA 3R hot-rolled steel

Complementary

Height	27.40 in (695.96 mm)
Width	51.20 in (1300.48 mm)
Depth	13.5 in (342.9 mm)
Product Weight	725.87 lb(US) (329.25 kg)

Ordering and shipping details

Category	US10PE216275
Discount Schedule	0PE2
GTIN	3606487189442
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	13.50 in (34.3 cm)
Package 1 Width	27.40 in (69.6 cm)
Package 1 Length	51.02 in (129.6 cm)
Package 1 Weight	824.7 lb(US) (374.1 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions

Use Again

 Repack and remanufacture	
Take-back	No