

PNOZ XV2 3/24VDC 2n/o 2n/o t

774502



Safety relay (standalone), inputs: 1/2-channel wiring with/without detection of shorts across contacts, outputs: 2 N/O, 2 N/Ot-d, UB = 24 V DC, width: 45 mm, screw terminals integrated, E-STOP monitoring, safety gates, with 2 delay-on de-energisation contacts, delay time can be set in 12 levels from 0.1 - 3 s.

Technical details

General data	
Approval:	CCC, CE, UKCA, cULus Listed, EAC (Eurasian), TÜV
Technical data	
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	0
RoHS exceptions:	0
RoHS except.s acc. to direct.:	6C, 7C I
REACH compliance:	1
REACH included substances:	Blei, Bleioxid
%-part of the pollutant:	> 0,1%
CAS No.:	7439-92-1, 1317-36-8
SCIP entry available:	yes
WEEE classification (08/2018):	U_KATEGORIE_5
Commercial data	
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27371819
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000019
ETIM Reference Feature:	EC001449

UNSPSC 25:	39122331
GTIN:	4046548011234
Volume:	0.529
Harmonized System Code:	85364900
Type of tariff number:	TARIC
Use of customs tariff number:	export, Import
Quantity per packaging unit:	1

Optional accessories

774090

COVER P-93

