

Replaced by HBL3P105NM, Surge
Protective Devices, SPIKESHIELD
Surface Mount Block, 100KA,
120/240V AC

By Hubbell Wiring Device-Kellems
Catalog # [HBL3W100C](#)

Surge Protective Devices, SPIKESHIELD Surface Mount Block,
100KA, 120/240V AC

Application

Surface Mount Brick with Leads

Performance

- Electrical - Diagnostics - Green Status LED's, Audible Alarm, Dry Contacts
- Electrical - Surge Current per Phase - 100kA
- Environmental - Operating Temperature - -40°F to 140°F (-40°C to 60°C)
- Mechanical - Terminal Accommodation - #10 AWG 18.0" Wire Leads

General

Catalog Number	HBL3W100C
EU RoHS Indicator	No
Environmental Conditions	Indoor and Outdoor
Indicator(s) Type	Green Status LED, Audible Alarm
Item Type	Wired-In Branch Panel Protection
Material	Steel
Material - Mounting Hardware	Mounting Screws
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	-40 Degrees F to 149 Degrees F (-40 C to 65 C)
Response Time	5
Series	Wired-In Panels
Specifications	- Dimensions - 3.1"D x 9.9"W x 4.8"H - Frequency - 50/60 Hz - NEMA - Type 4X - Warranty - 10 year - Weight - 4.78 lbs
Type	100kA



UPC 783585120782

Dimensions

Display Size 100kA Peak

Electrical Ratings

Connectivity	Leads
Frequency Rating	60 Hz
Phase	Single Phase
Voltage Rating	- Single Phase 120 VAC - Single Phase 240 VAC
Voltage Rating Description	120/240 VAC Single Phase

Certifications And Compliance

Industry Standard(s)	cULus UL1449-3Rd Edition Type 2 Spd
----------------------	--

Logistics

Carton Quantity 1

Product Assets

- [Catalog Page - WDK M-6 Catalog Page](#)
- [Catalog Page - WDK M-22 Catalog Page](#)
- [Catalogs - WDK Catalog Full 2024](#)
- [Engineering Drawing - HBL3W100C AutoCAD Drawing](#)
- [Installation Manuals - WIRING_PD_HBLxW100C_INSTALLINST](#)
- [Literature - Healthcare Product Solutions](#)
- [Literature - SpikeShield® Power Quality Surge Protective Devices](#)
- [Literature - Industrial Solutions](#)
- [Sales Drawings - WDK_HBL3W100C_DRAWING_PDF](#)
- [Specifications - HBL3W100C](#)
- [Warranty - SPD Series: 320kA, 160kA, 100kA, 120kA, 80MkA & 50kA](#)