

Surge Protective Devices,
SPIKESHIELD TVSS Plug Strips, 15A
125V, 6 Outlet with Telephone/Fax,
6' Cord, Office White

By Hubbell Wiring Device-Kellems
Catalog # [HBL6PS1050MA](#)

Surge Protective Devices, SPIKESHIELD TVSS Plug Strips, 15A
125V, 6 Outlet with Telephone/Fax, 6' Cord, Office White

Features

- 1050 joule, 6 foot cord, \$5,000 down-line warranty
- Tamper tamper resistant shutters.

Application

- 6 Outlet, Standard Devices

Performance

- Electrical - Max Surge Current - 19.5kA
- Electrical - Max. Operating Voltage - 130
- Electrical - Operating Frequency - 50/60Hz
- Environmental - Operating Temperature - -40°F to 160°F (-40°C to 70°C)

General

Catalog Number	HBL6PS1050MA
Color	Office White
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Indicator(s) Type	LED Indicator
Item Type	Surge Protection Plug Strips
Material	Non-Metallic
Material - Mounting Hardware	Portable
Number Of Outlets	6
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)
Outlet	Straight Blade 5-15R
Response Time	5
Series	Economy Surge Strips



Specifications	Length - 11.2" (284.5)
Type	Non-Metallic
UPC	783585120546

Dimensions

Display Size	1050 Joules
--------------	-------------

Electrical Ratings

Connectivity	Plug-In
Current / Amperage Rating	15 A
Current Rating	15 A
Frequency Rating	60 Hz
Phase	Single Phase

Conductor Related

Cord Length	6 ft
-------------	------

Logistics

Carton Quantity	12
Pallet Quantity	480

Product Assets

[Catalog Page - WDK M-9 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)
[Engineering Drawing - HBL6PS1050MA AutoCAD Drawing](#)
[Installation Manuals - WIRING_PD2380_INSTALLINST](#)
[Literature - SpikeShield® Power Quality Surge Protective Devices](#)
[Sales Drawings - WDK_HBL6PS1050_DRAWING_PDF](#)
[Specifications - HBL6PS1050MA](#)
[Warranty - Surge Plug Strips](#)