

Surge Protective Devices,
SPIKESHIELD TVSS Plug Strips, 15A
125V, 7 Outlet, 150 Joules, 6' Cord,
Office White

By Hubbell Wiring Device-Kellems
Catalog # [HBL7PS1050A](#)

Surge Protective Devices, SPIKESHIELD TVSS Plug Strips, 15A
125V, 7 Outlet, 150 Joules, 6' Cord, Office White

Application

- 7 Outlet, Standard Devices

Performance

- Electrical - Max Surge Current - 19.5kA
- Electrical - Max. Operating Voltage - 130
- Electrical - Operating Frequency - 50/60Hz
- Environmental - Operating Temperature - -40°F to 160°F (-40°C to 70°C)

General

Catalog Number	HBL7PS1050A
Color	Office White
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Indicator(s) Type	LED Indicator
Item Type	Surge Protection Plug Strips
Material	Non-Metallic
Material - Mounting Hardware	Portable
Number Of Outlets	7
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)
Outlet	Straight Blade 5-15R
Response Time	5
Series	Economy Surge Strips
Specifications	- Color - Off. White - Height - 1.85" (47.0) - Housing - ABS - Length - 14.75" (374.7)



Type	• Width - 2.36" (59.9)
UPC	Non-Metallic 783585120553

Dimensions

Display Size	1050 Joules
--------------	-------------

Electrical Ratings

Connectivity	Plug-In
Current / Amperage Rating	15 A
Current Rating	15 A
Frequency Rating	60 Hz
Phase	Single Phase

Conductor Related

Cord Length	6 ft
-------------	------

Logistics

Carton Quantity	10
Pallet Quantity	420

Product Assets

- [Catalog Page - WDK M-9 Catalog Page](#)
- [Catalogs - WDK Catalog Full 2024](#)
- [Engineering Drawing - HBL7PS1050A AutoCAD Drawing](#)
- [Installation Manuals - WIRING_PD2380_INSTALLINST](#)
- [Literature - SpikeShield® Power Quality Surge Protective Devices](#)
- [Sales Drawings - WDK_HBL7PS1050A_DRAWING_PDF](#)
- [Specifications - HBL7PS1050A](#)
- [Warranty - Surge Plug Strips](#)