

Surge Protective Devices,
SPIKESHIELD TVSS Plug Strips, 15A
125V, 8-Outlet with Telephone/Fax,
2100 Joules, 6' Cord, Office White

By Hubbell Wiring Device-Kellems
Catalog # [HBL8PS2100MA](#)

Surge Protective Devices, SPIKESHIELD TVSS Plug Strips, 15A
125V, 8-Outlet with Telephone/Fax, 2100 Joules, 6' Cord, Office
White

Performance

- Electrical - Max Surge Current - 39.0kA
- Electrical - Max. Operating Voltage - 130
- Electrical - Operating Frequency - 50/60Hz
- Environmental - Operating Temperature - -40°F to 160°F
(-40°C to 70°C)

General

Catalog Number	HBL8PS2100MA
Color	Office White
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Indicator(s) Type	LED Indicator
Item Type	Surge Protection Plug Strips
Material	Non-Metallic
Material - Mounting Hardware	Portable
Number Of Outlets	8
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)
Outlet	Straight Blade 5-15R
Response Time	5
Series	Economy Surge Strips
Specifications	- Color - Off. White - Cord Length - 6 Inch - Housing - ABS - Joule Rating - 2100 - No.of Outlets - 8
Type	Non-Metallic



UPC 783585120584

Dimensions

Display Size 2100 Joules

Electrical Ratings

Connectivity	Plug-In
Current / Amperage Rating	15 A
Current Rating	15 A
Frequency Rating	60 Hz
Phase	Single Phase

Conductor Related

Cord Length 6 ft

Logistics

Carton Quantity	20
Pallet Quantity	504

Product Assets

[Catalog Page - WDK M-9 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)
[Engineering Drawing - HBL8PS2100MA AutoCAD Drawing](#)
[Installation Manuals - WIRING_PD2380_INSTALLINST](#)
[Literature - SpikeShield® Power Quality Surge Protective
Devices](#)
[Sales Drawings - WDK_HBL8PS2100MA_DRAWING_PDF](#)
[Specifications - HBL8PS2100MA](#)
[Warranty - Surge Plug Strips](#)