



YH8C8CWCC, Compression H-Tap, Main #8-#14 AWG, Tap #8-#14 AWG, includes clear cover

By Burndy
Catalog # [YH8C8CWCC](#)



Copper Compression H Tap, Tin Plated, Accommoding the following wire sizes - Run (Main): 8 AWG-14 AWG Class B,C, 8 AWG-14 AWG Class I, DLO, Tap 1: 8 AWG-14 AWG Class B,C, 8 AWG-14 AWG Class I, DLO, kitted with clear cover. See sale drawing for metric wire size accommodates

Features

- Uninsulated compression H-tap connector, tin-plated
- Designs with more than one tap wire groove require installers to utilize a minimum of one Main (Run) and one Tap groove, other grooves can be left empty
- 'Third Hand' is a string provided with the H-tap connector and is used to wrap the wire while being inserted into the run and tap grooves
- H-tap connectors can be purchased separately or kitted with covers
- YH is connector sold separately without cover
- YH-WC is kitted H-tap connector and black cover
- YH-WCC is kitted H-tap connector and clear cover

Application

Wire Tap

General

Catalog Number	YH8C8CWCC
Color Code	Green
Connector Type	H-TAP W/CLR COVER
Die Index	11
EU RoHS Indicator	Yes
Finish Type	Tin-Plated
Material	COPPER
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	CRIMPIT
Temperature Rating	194
Trade Name	CRIMPIT™
Type	Compression Taps
UPC	781810436530
UPC 12 Digit	7818104365300

Dimensions

Dimension - L Length Overall	15 mm
mm	

Dimension - Length Overall	0.60 in
inch	
Dimension - Strip Length inch	3/4
Dimension - Width inch	0.63 in

Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

Conductor Related

Conductor - Copper Flex G Run	14;8
Conductor - Copper Flex G Tap	14;8
Conductor - Copper Flex H Tap	14;8
Conductor - Copper Flex I Run	8 AWG-14 AWG
Conductor - Copper Flex I Tap	14;8
Conductor - Copper Flex I Tap	8 AWG-14 AWG
Range	
Conductor - Copper Flex K Run	14;8
Conductor - Copper Flex K Tap	14;8
Conductor - Copper Flex M Run	14;8
Conductor - Copper Flex M Tap	14;8
Conductor - Copper Str Run	14;12;10;9;8
Conductor - Copper Str Run	8 AWG-14 AWG
Range	
Conductor - Copper Str Tap	14;12;10;9;8
Conductor - Copper Str Tap	8 AWG-14 AWG
Range	
Conductor - Material	COPPER
Conductor Type	CODE/FLEX

Certifications And Compliance

Buy American Compliant	Yes
Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - RoHS Compliance	CM
Status	

UL Listed	Yes	Catalogs - BURNDY Master Catalog - Section C - Compression Connections
Logistics		Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Carton Quantity	100	Customer Notices - Prop 65 Notice
Minimum Pack Quantity	1	Interactive Catalog - BURNDY Full-Line Digital Catalog
Pallet Quantity	3300	Product Cross Section Image(s) - BUR_YH2929WCC_LineArt
Product Assets		Sales Drawings - SD..206566-01
		Specifications - YH8C8CWCC

