

INSULATION PIERCING CONNECTORS-IPC

Galvan IPC Series connectors are an easy fit in copper-to-copper, copper-to-aluminum and aluminum-to-aluminum applications. Designed for splice or tap use, these units are not recommended for use with extra-flexible cables. The connectors are fully insulated and safe to install without special tools. IPC connectors eliminate time spent on wire stripping, taping and covers.

Buy Retail Online @ Galvan Direct



E155274

CATALOG NUMBER	CONDUCTOR RANGE		NO. BOLTS	PCS. PER CTN.	WT. PER 100
	Main AWG	Tap AWG			
IPC-1/0-2	1/0-8	2-10	1	6	30
IPC-1/0-1/0	1/0-8	1/0-8	1	6	30
IPC-2/0-10	2/0-4	10-14	1	6	23
IPC-4/0-2	4/0-3	2-10	1	6	26
IPC-4/0-2/0	4/0-2	2/0-6	1	4	41
IPC-4/0-4/0	4/0-2	4/0-4	1	4	43
IPC-350-350	350-1/0	350-1/0	2	2	111

CATALOG NUMBER	CONDUCTOR RANGE		NO. BOLTS	PCS. PER CTN.	WT. PER 100
IPC-500-4/0	500-2/0	4/0-4	2	2	116
IPC-500-350	500-4/0	350-1/0	2	2	111
IPC-750-500	750-250	500-250	2	2	166

- Wire range: #14 AWG to 750 MCM
 - Versatile and reliable
 - Use only with insulated conductors
 - Installs without tape, stripping or cover
 - Easy one-person installation
 - UL 486B listed
 - Rated: 600 volts, 90° C
-