

TCSMCN1M1F2

Radio frequency identification XG, Modbus shielded cable, M12 male connector, M12 female connector, IP67, 2 m

Main

Range of Product	Telemecanique Radio frequency identification XG
Accessory / separate part category	Connection accessories
Accessory / separate part type	Connecting cable
Accessory / separate part designation	Modbus shielded connecting cable
Accessory / separate part destination	Compact station Tap-off box
Cable length	6.6 ft (2 m)

Complementary

Electrical connection	1 female connector M12 straight A coding 1 male connector M12 straight A coding
Color	Black
Net Weight	0.254 lb(US) (0.115 kg)

Environment

IP Degree of Protection	IP67
-------------------------	------

Ordering and shipping details

Category	US10DS222490
Discount Schedule	0DS2
GTIN	3389119018463
Returnability	No
Country of origin	PL

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2.000 cm)
Package 1 Width	7.48 in (19.000 cm)
Package 1 Length	7.68 in (19.500 cm)
Package 1 Weight	5.362 oz (152.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	16
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	6.270 lb(US) (2.844 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Diisodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------