

EdgeConnect™, Straight Blade
Devices, Connector,
Industrial/Commercial Grade, 2-
Pole 3-Wire Grounding, 15A 125V, 5-
15R, Black and White

By Hubbell Wiring Device-Kellems
Catalog # [HBL5269CST](#)



EdgeConnect™, Straight Blade Devices, Connector,
Industrial/Commercial Grade, 2-Pole 3-Wire Grounding, 15A
125V, 5-15R, Black and White

Application

Extra Heavy Duty Industrial/Commercial Grade

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94 V-2
- Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact)
- Mechanical - Product Identification - Ratings are a permanent part of the device
- Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

General

Catalog Number	HBL5269CST
Color	Black and White
Cord Range	0.230"-0.720"(5.8-18.3)
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Horsepower - Maximum	0.5
Insulation	Insulated Body
Item Type	Insulgrip® Connector
Material	Nylon
Material - Mounting Hardware	Cord Mounted
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Series	EdgeConnect™
Size	3.28 in x 1.41 in x 1.09 in
Specifications	Body - Nylon, Retainer - Polycarbonate, Cover - Nylon, Cord Clamp - Nylon, Contact Blades - Copper Alloy, Spring -

Style
Temperature Rating

Type
UPC

Dimensions

Display Size
Weight

Standard Sized Product
0.2 lb

Electrical Ratings

Connectivity
Current / Amperage Rating
Dielectric Strength
Phase
Voltage Rating

Spring Termination
15 A
Withstands 2,000V minimum
Single Phase
125 V

Conductor Related

Conductor Range
Cord Type
Number Of Wires
Number of Conductors
Wire Size

#14 AWG to #10 AWG
All Listed Portables
3-Wire
3-Wire Grounding
#14 AWG to #10 AWG

Certifications And Compliance

Industry Standard(s)

- CSA Certified to C22.2 No. 42 File 280
- Fed. Spec. W-C596G
- NEMA® WD-6 Compliant

Nema Rating

5-15P

Logistics

Carton Quantity

10

Stainless Steel, Plunger - Nylon,
Drive/Assembly/Cord Clamp
Screws - Steel
Standard
Maximum continuous 75°C;
minimum -40°C (w/o impact)
Connectors
783585965321

Product Assets

[Catalog Page - WDK A-39 Catalog Page](#)

[Catalogs - WDK Catalog Full 2024](#)

[Installation Manuals - PD3069_Installation Manual](#)

[Literature - EdgeConnect™ Technology FAQ](#)

[Literature - EdgeConnect™ Technology](#)

[Literature - EdgeConnect™ Termination vs Standard Push Wire](#)

[Sales Drawings - M14757](#)

[Specifications - HBL5269CST](#)

[Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
WDK-HBL5269CST-SPEC-EN | REV 10/2024