

Straight Blade Devices, Tamper
Resistant, Duplex Receptacle,
Hubbell-Pro, Hospital Grade, 15A
125V, 2-Pole 3- WireGrounding, 5-
15R, White

By Hubbell Wiring Device-Kellems
Catalog # 8200WTRA



Straight Blade Devices, Tamper Resistant, Duplex Receptacle,
Hubbell-Pro, Hospital Grade, 15A 125V, 2-Pole 3- WireGrounding,
5-15R, White

Application

- Hubbell-Pro Heavy Duty Hospital Grade

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94V-2
- Environmental - Operating Temperature - Maximum continuous 75°C, minimum -40°C (w/o impact)
- Mechanical - Product Identification - Ratings are a permanent part of the device
- Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

General

Catalog Number	8200WTRA
Color	White
EU RoHS Indicator	Contact Manufacturer
Horsepower - Maximum	0.5
Item Type	Traditional Duplex
Material	Nylon
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Series	Hubbell-Pro
Specifications	• Automatic Self-grounding Staple - Stainless steel • Base - PBT • Clamping Plate - Plated steel • Face - Nylon • Ground Contacts - Brass

Style
Type
UPC

- Mounting Screws - Zinc plated steel
 - Mounting Strap - Galvanized steel
 - Power Contacts - Brass
- Smooth Face
Receptacle
783585542225

Dimensions

Dimensions	3.28 in x 1.57 in x 1.15 in
Height	1.15 in
Length	3.28 in
Weight	0.2 lb
Width	1.57 in

Electrical Ratings

Amperage Rating	15 A
Connectivity	Back and Side Wired
Current / Amperage Rating	15 A
Current Rating	15 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 VAC
Voltage Rating Description	125 V
Wattage	1875 W

Conductor Related

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG

Certifications And Compliance

Industry Standard(s)	• Certified to CSA, C22.2, No. 42 File 285 • Fed. Spec. W-C-596 • NEMA® WD-6 Compliant
----------------------	--

	UL Listed to UL498 File No. E2186
Nema Rating	5-15R

Logistics

Carton Quantity	10
-----------------	----

Product Assets

- Catalog Page - WDK A-27 Catalog Page
- Catalog Page - WDK L-8 Catalog Page
- Catalogs - WDK Catalog Full 2024
- Literature - Tamper-Resistant Receptacles for Healthcare

- Literature - Heavy Duty Tamper-Resistant Receptacles
- Literature - Duct Products Guide
- Literature - Tamper-Resistant Receptacles
- Literature - Healthcare Product Solutions
- Literature - Hubbell-Pro Hospital Grade Receptacles
- Literature - Hubbell-PRO Hospital Grade TR Receptacles
- Literature - Healthcare Application Guide
- Literature - Hubbell SystemOne Recessed Fire-Rated Poke-Throughs
- Literature - Emergency Preparedness for Healthcare
- Specifications - 8200WTRA
- Warranty - Industrial & Commercial Products
- Video - Tamper-Resistant Receptacles

