

lithium battery with cable and plug, for IPC227D, IPC277D, IPC427D, IPC477D, IPC477D-PRO, IPC427C, scope of supply: 1 lithium battery with cable and plug



Figure similar

| General information                               |                                                                                         |
|---------------------------------------------------|-----------------------------------------------------------------------------------------|
| Product type designation                          | Button cell BR-1/2 AA                                                                   |
| Installation type/mounting                        |                                                                                         |
| Wall mounting/direct mounting                     | Yes; in HMI devices, battery compartment                                                |
| Supply voltage                                    |                                                                                         |
| Type of supply voltage                            | DC                                                                                      |
| Rated value (DC)                                  | 3 V                                                                                     |
| Accumulator                                       |                                                                                         |
| Charge status display                             | No                                                                                      |
| Rechargeable                                      | No                                                                                      |
| Capacity                                          | 1 A·h                                                                                   |
| Lithium-ion                                       | No; Type: lithium-poly-carbonmonofluoride                                               |
| Special design                                    | Yes; With cable and connector                                                           |
| Ambient conditions                                |                                                                                         |
| Ambient temperature during operation              |                                                                                         |
| • min.                                            | 0 °C                                                                                    |
| • max.                                            | 55 °C                                                                                   |
| Ambient temperature during storage/transportation |                                                                                         |
| • min.                                            | -20 °C; shelf life at room temperature is 10 years with a capacity loss of 1 % per year |
| • max.                                            | 70 °C; shelf life at room temperature is 10 years with a capacity loss of 1 % per year  |
| Relative humidity                                 |                                                                                         |
| • Operation, max.                                 | 90 %                                                                                    |
| • Condensation permissible                        | No                                                                                      |
| Cables                                            |                                                                                         |
| Cable length                                      | 110 mm                                                                                  |
| Dimensions                                        |                                                                                         |
| Length                                            | 25 mm                                                                                   |
| Diameter                                          | 15 mm                                                                                   |
| Weights                                           |                                                                                         |
| Weight (without packaging)                        | 12 g                                                                                    |
| Weight (with packaging)                           | 14 g                                                                                    |
| Scope of supply                                   |                                                                                         |
| Delivery quantity in pieces                       | 1                                                                                       |
| Other                                             |                                                                                         |
| printable with laser printer                      | No                                                                                      |
| Merchandise                                       | Yes; BR-1/2AA                                                                           |
| Manufacturer name                                 | On request                                                                              |

|                                  |                                                              |
|----------------------------------|--------------------------------------------------------------|
| Manufacturer's address           | On request                                                   |
| Target devices                   | For IPC227D, IPC277D, IPC427D, IPC477D, IPC477D PRO, IPC427C |
| Note:                            | Dispose of battery (lithium) properly; hazardous product!    |
| Usable in the following products |                                                              |
| • Product 1                      | 6AV7881-*                                                    |
| • Product 2                      | 6AV7240-*                                                    |
| • Product 3                      | 6AV7250-*                                                    |

last modified:

5/14/2024 