

Style Line® Decorator Series
Specification Grade Nightlight
Switches

By Hubbell Wiring Device-Kellems
Catalog # [DS120NLGY](#)



Style Line® decorator nightlight switch, back and side wired

Features

- LED light activated when low levels of ambient light are detected by photosensor
- Optimal lens size for greater illumination
- Impact resistant thermoplastic rocker

Performance

- Electrical-Color Temperature:3400K - 3600K
- Dielectric Voltage-Withstands 1500V AC minimum for 1 minute
- LED Energy Consumed-0.5 watt
- Light Output-0.5 Lumens
- Load Capacity-20A, 120VAC
- Overload-Minimum 4.8 times rated current for 100 cycles
- Temperature Rise-30°C maximum at rated current
- Mechanical-Terminal Accommodations-#14-#10 AWG copper stranded or solid conductor only
- Environmental-Flammability- UL 94V-2
- Environmental-Operating Temperature-Max. continuous: 75°C
- Min. continuous: -40°C without impact

General

Catalog Number	DS120NLGY
Color	Gray
EU RoHS Indicator	Contact Manufacturer
Specifications	• Rocker Material- Thermoplastic

- Lens-Polycarbonate
- Base-Thermoplastic
- Contacts-Brass Alloy
- Mounting Strap-Zinc Plated Steel
- Terminal Screws-Plated Steel
- Automatic Self-grounding Staple- Stainless steel
- Mounting Screws-Zinc Plated Steel

UPC

783585186832

Certifications And Compliance

Industry Standard(s)	UL Listed
----------------------	-----------

Logistics

Carton Quantity	10
-----------------	----

Product Assets

- [Catalog Page - WDK D-16 Catalog Page](#)
- [Catalog Page - WDK Z-3 Catalog Page](#)
- [Catalogs - WDK Catalog Full 2024](#)
- [Installation Manuals - WIRING_PD2444_PD2548_INSTALLINST](#)
- [Sales Drawings - WDK_DS120NL_DRAWING_PDF](#)
- [Specifications - DS120NLGY](#)
- [Warranty - Industrial & Commercial Products](#)