



**SKU:** NBAS-003-1-A

**UPC:** 0783669005523

**Features & Benefits:**

**Description:** Aluminum Neutral Bar, Dual Rated, Conductor Range 4-14, 3 Ports, 1 Hole, #10 Bolt, Headed Slot Drive, UL, CSA

## Specs

### Additional Class Attributes

|                            |            |
|----------------------------|------------|
| Connection                 | Mechanical |
| Mounting Hole Type         | Thru       |
| Number of Conductors       | 3          |
| Number of Mounting Holes   | 1          |
| Number of Poles            | 1          |
| Number of Ports / Wireways | 4          |
| Number of Usable Ports     | 3          |
| Type of Accessory          | NBST-2/0   |

### Dimensions

|                              |         |
|------------------------------|---------|
| Dimension G (IN)             | 0.804   |
| Dimension G (mm)             | 20.4216 |
| Drive Size Main              | NA      |
| Drive Type Main              | Slotted |
| Height (IN)                  | 0.622   |
| Height BX (IN)               | 1.9     |
| Height (mm)                  | 15.7988 |
| Length (IN)                  | 1.296   |
| Mounting Bolt/Stud Size (mm) | 254     |
| Mounting Hole Diameter (IN)  | 0.203   |
| Mounting Hole Position (IN)  | 3       |
| Weight (LB)                  | 0.027   |
| Weight BX (LB)               | 0.635   |
| Width (IN)                   | 0.312   |
| Width BX (IN)                | 4       |

### Material and Finish

|                                |                      |
|--------------------------------|----------------------|
| Conductor Material             | Copper               |
| Connector Finish               | Tin                  |
| Insulation                     | NA                   |
| Material                       | Aluminum             |
| Wire Binding Hardware Finish   | Yellow Zinc Chromate |
| Wire Binding Hardware Material | Steel                |

### Additional Technical Specifications

Conductor Type

Solid

### Bolt and Screw Sizes

|                                        |                |
|----------------------------------------|----------------|
| Mounting Bolt/Stud Size                | #10            |
| Number of Wire Binding Screws per Port | 1              |
| Wire Binding Screw Size                | 1/4            |
| Wire Binding Torque                    | 4 - 6 AWG = 35 |

### General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 1               |
| Carton Quantity Description | STD PACK QTY 20 |
| Dual Rated                  | Yes             |
| NEMA Code                   | S-588-3         |
| UPC Code                    | 78366900552     |

### Testing Standards

|                          |                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| CSA File Number          | LR-29601                                                                                                            |
| CSA Standard             | C22.2 No. 65-03                                                                                                     |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| UL Control Number        | NA                                                                                                                  |
| UL / CULUS Specification | UL 486A/B Recognized                                                                                                |
| UL File Number           | E6207                                                                                                               |

### Color

|       |        |
|-------|--------|
| Color | Silver |
|-------|--------|

### Conductor Ranges

|                                                        |                 |
|--------------------------------------------------------|-----------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA              |
| Conductor Range AL Stranded (Primary, run, main, line) | 4 Str - 14 Str  |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA              |
| Conductor Range CU Solid (Primary, run, main, line)    | 10 Sol - 14 Sol |
| Conductor Range CU Solid (Secondary, tap, load)        | NA              |
| Conductor Range CU Stranded (Primary, run, main, line) | 4 Str - 14 Str  |
| Conductor Range CU Stranded (Secondary, tap, load)     | NA              |
| Conductor Range AL Solid (Primary, run, main, line)    | 10 Sol - 14 Sol |

### Voltage

|                |       |
|----------------|-------|
| Voltage Rating | 35 kV |
|----------------|-------|