

# Product data sheet

## Characteristics

# 8911DP SG43V07

Starter, Definite Purpose, nonreversing, 40A,  
3 pole, 3 phase, 600 VAC coil, melting alloy  
overload, NEMA 1, +options



## Main

|                         |                                                                                                                                     |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Product                 | Definite Purpose Starter                                                                                                            |
| Ampere Rating           | 40 A                                                                                                                                |
| Horsepower Rating       | 3 Hp 115 V AC, 1 phase<br>10 Hp 230 V AC, 3 phase<br>7.5 Hp 230 V AC, 1 phase<br>20 Hp 460 V AC, 3 phase<br>25 hp 575 V AC, 3 phase |
| Maximum Voltage Rating  | 600 V AC                                                                                                                            |
| Control Circuit Voltage | 550 V AC 50 Hz<br>600 V AC 60 Hz                                                                                                    |
| Phase                   | 3 phase                                                                                                                             |

## Complementary

|                         |                                                    |
|-------------------------|----------------------------------------------------|
| Enclosure Material      | Painted sheet steel                                |
| Enclosure Rating        | NEMA 1                                             |
| Locked Rotor Amperes    | 240 A 230 V AC<br>200 A 460 V AC<br>160 A 575 V AC |
| Number of Poles         | 3P                                                 |
| Range                   | DPS                                                |
| Overload Type           | Melting alloy                                      |
| Number of Thermal Units | 3                                                  |

## Ordering and shipping details

|                       |                        |
|-----------------------|------------------------|
| Category              | 21381-8911 DP          |
| Discount Schedule     | CP1                    |
| GTIN                  | 785901001508           |
| Nbr. of units in pkg. | 1                      |
| Package weight(Lbs)   | 5.88 lb(US) (2.667 kg) |
| Returnability         | Yes                    |
| Country of origin     | CN                     |

## Packing Units

|                        |                     |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE                 |
| Package 1 Height       | 6.50 in (16.51 cm)  |
| Package 1 width        | 6.50 in (16.51 cm)  |
| Package 1 Length       | 11.50 in (29.21 cm) |

## Offer Sustainability

|                            |                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| REACH Regulation           |  <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                                                               |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|