

Pedestal, 6-Gang, Black

By Hubbell Wiring Device-Kellems
Catalog # [FR680BKA](#)



In-Floor Delivery Systems, Fire-Rated Poke-Throughs, Pedestal,
6-Gang , Black

Features

- 1-4 hour fire rating (1-3 hour for steel floor units and concrete topping, D900 Series Design)
- For 2 1/4 in. to 7 in. floor thickness
- Approved for use in the City of Chicago

Application

FRPT Pedestal

Performance

Electrical - Service Pedestal Construction - Heavy gauge galvanized steel frame with aluminum housing and face plates

General

Catalog Number	FR680BKA
EU RoHS Indicator	No
Finish Type	Black
Item Type	6-Gang Above Floor Service Fittings
Knockouts	None
Material	Aluminum
Material - Mounting Hardware	On PT27A or PT7XC Through Floor Fitting
Mounting Hardware	Included
OEM Brand Name	Hubbell Wiring Device-Kellems

Specifications

- Cubic Inch Capacity - 117.00 in. (1916.4cm³)
- Housing - Painted aluminum
- Pedestal Finish - Textured black or gray epoxy paint
- Power Capacity - 58.5 in. (958.2cm³)
- Voice/Data - 58.5 in. (958.2cm³)

Style
UPC

Pedestals
783585396217

Dimensions

Display Size

Standard Sized Product

Certifications And Compliance

Industry Standard(s)

UL Listed

Product Assets

- [Catalog Page - WDK P-34 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)
[Literature - Delivery Systems Product Guide](#)
[Sales Drawings - WDK_FR680BKA_DRAWING_PDF](#)
[Specifications - FR680BKA](#)
[Warranty - Industrial & Commercial Products](#)