



Small size ideal for junction box mounting in wireless or other modern lighting control systems. Integral test switch and LED allows for quick testing and verification of proper functionality.

Color: White

Weight: 0.0 lbs

Project:	Type:
Prepared By:	Date:

Technical Specifications

Compliance

UL Listed:

UL924 Listed

Electrical

Installation:

All Lightcloud components should be installed by a licensed electrician in accordance with local codes.

Sensing Input:

120V - 277V

Load Rating:

120V - 277V (20A)

Ballast Load Rating:

20A (120V - 277V)

Incandescent Load:

1200W (120V) / 1500W (277V)

Load:

Contact #1 20A (120V-277V)

Contact #2 1A (30V DC)

Mechanical

Mounting:

Fixture Mount

Rating:

UL94V-0A

Shipping Weight:

12 oz

Temperature:

32°F - 140°F (0°C - 60°C)

Size:

1.7" x 3" x 1.2" (W x H x D body)

Other

Warranty:

10-year full hardware warranty with 100% repair/replacement coverage for all properly installed devices. [See Lightcloud Warranty Terms.](#)

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

