



Main

Range	TeSys
Device short name	MN
Product or Component Type	Voltage release
Device Application	Control
Range compatibility	TeSys (TeSys GV4) TeSys (TeSys BV4)
Voltage release type	Undervoltage release
[Uc] control circuit voltage	110...130 V AC 50/60 Hz 125 V DC

Complementary

[Ui] rated insulation voltage	130 V IEC 60947-1
Threshold tripping voltage	< 0.35 Un failsafe opening 0.35...0.7 Un possible opening 0.85...1.1 Un enabled closing
Mounting Mode	Internal mounting
Maximum inrush power in VA	7 VA
Maximum inrush power in W	2 W
Maximum hold-in power consumption in VA	7 VA
Maximum hold-in power consumption in W	2 W
Mechanical durability	20000 cycles
Operating time	< 50 ms
Connections - terminals	Spring terminals 1 0.00...0.00 in ² (0.5...1.5 mm ²) flexible without cable end
Wire stripping length	0.31 in (8 mm)

Environment

Quantity per Set	Set of 1
------------------	----------

Ordering and shipping details

Category	22366-MAN STR PROTECTORS-GV1/GV3
Discount Schedule	I11
GTIN	3606485444833
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.34 in (3.400 cm)
Package 1 Width	2.44 in (6.200 cm)
Package 1 Length	3.35 in (8.500 cm)
Package 1 Weight	2.15 oz (61.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.46 in (8.800 cm)

Package 2 Width	5.12 in (13.000 cm)
Package 2 Length	7.28 in (18.500 cm)
Package 2 Weight	24.13 oz (684.000 g)
Unit Type of Package 3	S03
Number of Units in Package 3	160
Package 3 Height	11.81 in (30.000 cm)
Package 3 Width	11.81 in (30.000 cm)
Package 3 Length	15.75 in (40.000 cm)
Package 3 Weight	38.80 lb(US) (17.600 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.