

PNOZ X9 100-120VAC 24VDC 7n/o 2n/c 2so

774605



Safety relay (standalone), inputs: 1/2-channel wiring with detection of shorts across contacts, outputs: 7 N/O, 2 N/C, 2 SC, automatic/monitored start, UB = 24 V DC, width: 90 mm, screw terminals integrated, monitoring of E-STOP, safety gates. Suitable for control through SC outputs.

Technical details

General data

Approval: CE, CCC, UKCA, cULus Listed, EAC (Eurasian), TÜV

Technical data

Environment

RoHS directive: 2011/65/EU, 2015/863/EU

RoHS conformity: 0

RoHS exceptions: 0

RoHS except.s acc. to direct.: 7A

REACH compliance: 1

REACH included substances: Blei

%-part of the pollutant: > 0,1

CAS No.: 7439-92-1

SCIP entry available: yes

WEEE classification (08/2018): U_KATEGORIE_5

Commercial data

ECLASS version: ECLASS-13

ECLASS Reference Feature: 27371819

ETIM Version: ETIM-9.0

ETIM Reference Group: EG000019

ETIM Reference Feature: EC001449

UNSPSC 25:	39122331
GTIN:	4046548010695
Volume:	1.046
Harmonized System Code:	85364900
Type of tariff number:	TARIC
Use of customs tariff number:	export, Import
Quantity per packaging unit:	1