



# K22A36U2N, AL Universal Terminal, 2-Hole, 1/2" Stud, 1-3/4" NEMA Spacing

By Burndy  
Catalog # K22A36U2N

Aluminum Universal Terminal, 2 Hole, 1/2" diameter stud holes spaced 1-3/4" on center (NEMA-spacing), tin plated



### Features

- AL9CU Dual Rated for both copper an aluminum conductor
- Listed to UL Wire Connector Standard UL486A-486B
- 1/2" diameter stud holes spaced 1-3/4" on center (NEMA-spacing)
- 600 Volt Rated
- Range Taking conductor port

### Application

Terminate multiple conductors onto equipment pads, panel boards, or switchgear

### General

|                              |                         |
|------------------------------|-------------------------|
| Connector Type               | Stacked                 |
| Construction Material - Main | Aluminum                |
| EU RoHS Indicator            | Yes                     |
| Material                     | Aluminum                |
| Plated                       | Y                       |
| Plating Type                 | Tin - Electro Plated    |
| Temperature Rating           | 194                     |
| Trade Name                   | N                       |
| Type                         | Bolted Lugs & Terminals |
| UPC                          | 781810670156            |
| UPC 12 Digit                 | 7818106701566           |

### Dimensions

|                                 |                             |
|---------------------------------|-----------------------------|
| Dimension - Bolt Size fraction  | 1/2                         |
| Dimension - Hole Size mm        | 0 mm                        |
| Dimension - L Length Overall mm | 0 mm                        |
| Dimension - Thread Size         | -                           |
| Dimension - Width mm            | 0 mm                        |
| Dimensions                      | 5.34 in x 2.47 in x 3.00 in |
| Height                          | 3.00 in                     |
| Length                          | 5.34 in                     |
| Width                           | 2.47 in                     |

### Electrical Ratings

|                          |       |
|--------------------------|-------|
| Rating - Minimum Voltage | 600   |
| Voltage Rating           | 600 V |

### Conductor Related

|                |                                                                                         |
|----------------|-----------------------------------------------------------------------------------------|
| Conductor Type | <ul style="list-style-type: none"><li>• AL C Str-Size</li><li>• CU C Str-Size</li></ul> |
|----------------|-----------------------------------------------------------------------------------------|

### Certifications and Compliance

|                                    |              |
|------------------------------------|--------------|
| Certification - CSA Approved       | Yes          |
| Certification - ETL                | No           |
| Certification - UL Recognized      | N            |
| Certification - cULus              | N            |
| Industry Standard(s)               | UL 486A-486B |
| Standards - Industry Standards Met | UL 486A-486B |
| Standards - RoHS Compliance Status | EX           |
| UL Listed                          | Yes          |

### Logistics

|                       |   |
|-----------------------|---|
| Minimum Pack Quantity | 1 |
|-----------------------|---|

### Product Assets

[Catalogs - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Sales Drawings - 50094865](#)



A proud member of the Hubbell Family.

