



**SKU:** PICS-62

**UPC:** 0783669232851

**Features & Benefits:**

**Description:** Aluminum Insulated Service Entrance Sleeve, Dual Rated, Main Conductor Range 4 Sol - 6, Tap Range 8 Sol - 10, Blue Color Code, Die Index ND-BG

## Specs

### Additional Class Attributes

|                         |          |
|-------------------------|----------|
| Barrel Marking          | Ink      |
| Barrel Type             | Standard |
| Flared End              | No       |
| ILSCOs Die Index Number | ND-BG    |

### Dimensions

|                |                    |
|----------------|--------------------|
| Height (IN)    | 0.72               |
| Height BX (IN) | 2.75               |
| Height (mm)    | 18.288             |
| Length (IN)    | 2.81               |
| Length (mm)    | 71.374             |
| Weight (LB)    | 0.0436590137661021 |
| Weight BX (LB) | 3.612              |
| Width (IN)     | 0.72               |
| Width BX (IN)  | 6                  |
| Width (mm)     | 18.288             |

### Material and Finish

|                    |          |
|--------------------|----------|
| Conductor Material | Aluminum |
| Connector Finish   | NA       |
| Insulation         | Nylon    |
| Material           | Aluminum |

### Additional Technical Specifications

|                |       |
|----------------|-------|
| Conductor Type | Solid |
|----------------|-------|

### General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 1               |
| Carton Quantity Description | STD PACK QTY 50 |
| Direct Burial               | No              |
| Dual Rated                  | Yes             |
| NEMA Code                   | 0-000-1         |
| UPC Code                    | 78366923285     |

## Bolt and Screw Sizes

|                         |    |
|-------------------------|----|
| Mounting Bolt/Stud Size | NA |
|-------------------------|----|

## Testing Standards

|                    |                                                                                                                     |
|--------------------|---------------------------------------------------------------------------------------------------------------------|
| ANSI Specification | ANSI C119.4                                                                                                         |
| CSA File Number    | NA                                                                                                                  |
| Prop65 Compliance  | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| RUS Listed         | Yes                                                                                                                 |
| UL Control Number  | NA                                                                                                                  |
| UL File Number     | NA                                                                                                                  |

## Environment and Temperature

|                    |    |
|--------------------|----|
| Temperature Rating | NA |
|--------------------|----|

## Color

|                      |       |
|----------------------|-------|
| Color                | Black |
| Color Code           | Blue  |
| Color Code Secondary | Brown |

## Conductor Ranges

|                                                        |                |
|--------------------------------------------------------|----------------|
| Conductor Range ACSR (Secondary, tap, load)            | 6 ACSR         |
| Conductor Range ACSR (primary, run, main, line)        | NA             |
| Conductor Range AL Solid (Secondary, tap, load)        | 8 Sol - 10 Sol |
| Conductor Range AL Stranded (Primary, run, main, line) | 4 Str - 6 Str  |
| Conductor Range AL Stranded (Secondary, tap, load)     | 8 Str - 10 Str |
| Conductor Range CU Solid (Primary, run, main, line)    | 4 Sol          |
| Conductor Range CU Solid (Secondary, tap, load)        | 8 Sol - 10 Sol |
| Conductor Range CU Stranded (Primary, run, main, line) | 4 Str - 6 Str  |
| Conductor Range CU Stranded (Secondary, tap, load)     | 8 Str - 10 Str |
| Conductor Range AL Solid (Primary, run, main, line)    | 8 Sol - 10 Sol |