



SKU: SLUH-225

UPC: 0783669842470

Features & Benefits:

Description: Copper Mechanical Heavy Duty Lug Offset, Conductor Range 250-6, 1 Port, 1 Hole, 5/16in Bolt Size, UL, CSA

Specs

Additional Class Attributes

Collar Style	V-Bottom
Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1

Dimensions

Dimension G (IN)	0.5
Dimension G (mm)	12.7
Drive Size Main	1/4
Drive Type Main	Internal Hex
Height (IN)	1.453
Height BX (IN)	2
Height (mm)	36.9062
Length (IN)	2.448
Length (mm)	62.1792
Mounting Hole Diameter (IN)	0.344
Mounting Hole Diameter (mm)	8.7376
Tang Length (IN)	1.125
Tang Length (mm)	28.575
Tang Offset (IN)	0.806
Tang Offset (mm)	20.4724
Tang Thickness (IN)	0.156
Tang Thickness (mm)	3.9624
Tang Width (IN)	1
Tang Width (mm)	25.4
Weight (LB)	0.293
Weight BX (LB)	7.482
Width (IN)	1
Width BX (IN)	6.1875
Width (mm)	25.4

Material and Finish

Conductor Material	Copper
--------------------	--------

Connector Finish	Tin
Insulation	NA
Material	Copper
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Brass

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	5/16
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	5/8
Wire Binding Torque	200

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366984247

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA



Flex Conductor Range
Wire Combinations

3/0-6 G,H,I,K,M,DLO
NA

Voltage

Voltage Rating

35 kV