

# XB7NW34G1

Harmony XB7, Monolithic illuminated push button, plastic, red, Ø22, integral LED, spring return, 110...120 V AC, 1 NO



## Main

|                               |                                                                                                                                                                               |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of Product              | Harmony XB7                                                                                                                                                                   |
| Product or Component Type     | Illuminated push-button                                                                                                                                                       |
| Device short name             | XB7                                                                                                                                                                           |
| Mounting diameter             | 0.87 in (22 mm)                                                                                                                                                               |
| Sale per indivisible quantity | 10                                                                                                                                                                            |
| IP degree of protection       | IP20 IEC 60529 rear face)<br>IP65 IEC 60529 front face)                                                                                                                       |
| Shape of signaling unit head  | Round                                                                                                                                                                         |
| Type of operator              | Spring return                                                                                                                                                                 |
| Operator profile              | Red projecting, unmarked                                                                                                                                                      |
| Contacts type and composition | 1 NO                                                                                                                                                                          |
| Connections - terminals       | Screw clamp terminals, <= 2 x 1.5 mm <sup>2</sup> with cable end EN/IEC 60947-1<br>Screw clamp terminals, 1 x 0.34...2 x 2.5 mm <sup>2</sup> without cable end EN/IEC 60947-1 |
| Light source                  | LED                                                                                                                                                                           |
| Bulb base                     | Integral LED                                                                                                                                                                  |
| [Us] rated supply voltage     | 120 V AC 50/60 Hz                                                                                                                                                             |
| Device presentation           | Monolithic product                                                                                                                                                            |

## Complementary

|                                        |                                                                                                                                                                                   |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD overall width                      | 1.14 in (29 mm)                                                                                                                                                                   |
| CAD overall height                     | 1.14 in (29 mm)                                                                                                                                                                   |
| CAD overall depth                      | 2.26 in (57.5 mm)                                                                                                                                                                 |
| Terminals description ISO n°1          | (13-14)NO                                                                                                                                                                         |
| Net Weight                             | 0.05 lb(US) (0.023 kg)                                                                                                                                                            |
| Device mounting                        | Fixing hole 0.89 in (22.5 mm) 22.3 +0.4/0 EN/IEC 60947-1                                                                                                                          |
| Fixing center                          | >= 30 x 40 mm support panel) metal 0.04...0.24 in (1...6 mm)<br>>= 30 x 40 mm support panel) plastic 0.08...0.24 in (2...6 mm)                                                    |
| Fixing mode                            | Fixing nut beneath head 17.70...21.24 lbf.in (2...2.4 N.m)                                                                                                                        |
| Contact operation                      | Slow-break                                                                                                                                                                        |
| Positive opening                       | With (only NO)                                                                                                                                                                    |
| Mechanical durability                  | 300000 cycles                                                                                                                                                                     |
| Tightening torque                      | 7.08...10.62 lbf.in (0.8...1.2 N.m) EN 60947-1                                                                                                                                    |
| Shape of screw head                    | Cross JIS No 1<br>Cross Philips no 1<br>Cross pozidriv No 1<br>Slotted flat Ø 4 mm<br>Slotted flat Ø 5.5 mm                                                                       |
| Short-circuit protection               | 4 A cartridge fuse gG EN/IEC 60947-5-1                                                                                                                                            |
| [Ui] rated insulation voltage          | 250 V 3)EN/IEC 60947-1                                                                                                                                                            |
| [Uimp] rated impulse withstand voltage | 4 kV EN/IEC 60947-1                                                                                                                                                               |
| [Ie] rated operational current         | 0.1 A 250 V, DC-13, R300 EN/IEC 60947-5-1<br>0.22 A 125 V, DC-13, R300 EN/IEC 60947-5-1<br>0.3 A 240 V, AC-14, D300 EN/IEC 60947-5-1<br>0.6 A 120 V, AC-14, D300 EN/IEC 60947-5-1 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company Schneider Electric. It is not intended to be used as a substitute for the specific user manual of the product. It is the duty of any user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                        |                                                                                                                                                                                                                                                           |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical durability  | 1000000 Cycles, DC-13, 0.3 A 24 V 216000 cyc/mn 0.5 EN/IEC 60947-5-1 appendix C<br>1000000 Cycles, AC-15, 0.03 A 230 V 216000 cyc/mn 0.5 EN/IEC 60947-5-1 appendix C<br>1000000 cycles, AC-15, 0.09 A 240 V 108000 cyc/mn 0.5 EN/IEC 60947-5-1 appendix C |
| Electrical reliability | $\Lambda \leq 10 \exp(-6)$ 17 V 5 mA EN/IEC 60947-5-4                                                                                                                                                                                                     |
| Signalling type        | Steady                                                                                                                                                                                                                                                    |
| Supply voltage limits  | 100...132 V AC                                                                                                                                                                                                                                            |
| Current Consumption    | 12...17 mA                                                                                                                                                                                                                                                |
| Service life           | 70000 h at rated voltage and 25 °C                                                                                                                                                                                                                        |

## Environment

|                                       |                                                                                                     |
|---------------------------------------|-----------------------------------------------------------------------------------------------------|
| Protective treatment                  | TH                                                                                                  |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)                                                                          |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C)                                                                          |
| Electrical shock protection class     | Class II IEC 61140                                                                                  |
| NEMA degree of protection             | NEMA 12 UL 50 E                                                                                     |
| Standards                             | UL 508<br>EN/IEC 60947-1<br>CSA C22.2 No 14<br>JIS C8201-5-1<br>EN/IEC 60947-5-1<br>JIS C8201-1     |
| Product Certifications                | CCC<br>GOST                                                                                         |
| Vibration resistance                  | 5 gn 2...500 Hz)IEC 60068-2-6                                                                       |
| Shock resistance                      | 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27<br>30 gn 18 ms) half sine wave acceleration |
| Electromagnetic emission              | Class B EN 55011                                                                                    |

## Ordering and shipping details

|                       |                             |
|-----------------------|-----------------------------|
| Category              | 22464-PUSHBUTTONS, XB7-22MM |
| Discount Schedule     | CS2                         |
| GTIN                  | 3606480470813               |
| Nbr. of units in pkg. | 1                           |
| Package weight(Lbs)   | 0.88 oz (25.0 g)            |
| Returnability         | No                          |
| Country of origin     | ID                          |

## Packing Units

|                        |                  |
|------------------------|------------------|
| Unit Type of Package 1 | PCE              |
| Package 1 Height       | 2.36 in (6 cm)   |
| Package 1 width        | 1.26 in (3.2 cm) |
| Package 1 Length       | 1.26 in (3.2 cm) |


## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                             |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                       |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           |  <a href="#">REACH Declaration</a>                                                                                                                                                                       |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>                                                                                                        |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                         |
| RoHS exemption information |  <a href="#">Yes</a>                                                                                                                                                                                     |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>                                                                                                                                                                  |

|                             |                                                                                                                                |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Environmental Disclosure    | <a href="#"> Product Environmental Profile</a> |
| Circularity Profile         | <a href="#"> End Of Life Information</a>      |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.   |
| <b>Contractual warranty</b> |                                                                                                                                |
| Warranty                    | 18 months                                                                                                                      |

## Illuminated Pushbutton

### Dimensions



e Support panel thickness: 1 to 6 mm/0.4 to 0.24 in. (metal), 2 to 6 mm/0.8 to 0.24 in. (plastic).

## Mounting

### Diameter of Finished Fixing Holes



- (1) Minimum value.
- (2) 40 mm/1.58 in. for Emergency switching off pushbutton only.
- (3) Standard value: Ø 22.3 (0; + 0.4) mm/Ø 0.88 (0; + 0.02) in.

### “U” Type Tag Connection



- (1) 6.5 mm/0.26 in. recommended, 7 mm/0.28 in. max.
- (2) M3 screw clamp terminal.

---

## Wiring

---

