



Main

Range of Product	Harmony
Product or Component Type	Digital display body
[Us] rated supply voltage	24 V DC
Connections - terminals	Screw connectors, 0.5 x 2.5 mm ²

Complementary

Mounting support	panel
Device mounting	Fixing hole 0.88 in (22.3 mm)
Electronic decoding	Decimal + BCD
Supply voltage limits	13...30 V
Current consumption	<= 36 mA 30 V <= 40 mA 24 V
Protection Type	Reverse polarity protection
Logic input	Positive
Voltage state 0 guaranteed	-30...5 V
Voltage state 1 guaranteed	13...30 V
Current state 0 guaranteed	<= 1.4 mA
Current state 1 guaranteed	4...9.5 mA

Environment

Product Certifications	UL CSA
Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Vibration resistance	10 gn 10...500 Hz IEC 60068-2-6
Shock resistance	180 gn 11 ms IEC 60068-2-27
Electrical shock protection class	Class II IEC 60536 Class II NF C 20-030
IP degree of protection	IP65 conforming to IEC 60529 IP65 conforming to NF C 20-010

Ordering and shipping details

Category	22460-PUSHBUTTONS 22MM (PLASTIC)
Discount Schedule	CS2
GTIN	3389110648966
Nbr. of units in pkg.	1
Package weight(Lbs)	2.01 oz (57.0 g)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.18 in (3 cm)
Package 1 width	1.65 in (4.2 cm)
Package 1 Length	4.25 in (10.8 cm)
Unit Type of Package 2	S01
Number of Units in Package 2	30
Package 2 Weight	4.23 lb(US) (1.917 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------