

Product data sheet

Characteristics

8903SQH1V02

Contactor, Type S, multipole lighting,
electrically held, 100A, 2 pole, 110/120 VAC
50/60 Hz coil, NEMA 3R



Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	100 A
Number of Poles	2P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical Connection	Lugs
Height	25.31 in (643 mm)
Depth	8.62 in (219 mm)
Width	12.83 in (326 mm)

Environment

Enclosure Type	NEMA 3R Stainless Steel surface none
Product certifications	UL listed file E16151 CCN NRNT

Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	785901024033
Nbr. of units in pkg.	1
Package weight(Lbs)	9.75 lb(US) (4.424 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	25.31 in (64.3 cm)
Package 1 width	12.83 in (32.6 cm)
Package 1 Length	8.62 in (21.9 cm)

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------