

Main

Range of Product	9012G
Pressure sensor type	Electromechanical pressure switch
Pressure sensor name	9012G
Pressure Rating	1000 psi (6894.8 kPa)
Maximum pressure	10000 psi
Contacts type and composition	NC-NO, SPDT-DB, Form Z, snap action, silver nickel contacts
Controlled fluid	Hydraulic oil -26...121 °C (-15...250 °F)) Non-corrosive liquids -26...121 °C (-15...250 °F)) Air -26...121 °C (-15...250 °F)) Non-corrosive gas -26...121 °C (-15...250 °F))
Fluid connection type	0.25 inch 18 NPTF UL 508
Pressure switch type of operation	Regulation between 2 thresholds
Scale type	Adjustable differential
Local display	With range scale window

Complementary

Range on decreasing pressure	20...1000 psi (137.9...6894.8 kPa)
Approx adjustable differential at mid range	59...200 psi (406.8...1379.0 kPa) +/- 2.5 % full scale
Terminal block type	4 screw terminals
Electrical connection	1 male connector mini) 5 pins
Terminal identifier	(2-4)NC
Electrical circuit type	Control circuit
Local signalling	1 neon clear) 120 V AC/DC 105...125 V)
Line Rated Current	0.22 A 125 V DC 3 A 120 V AC
Setting	Internal
Enclosure Material	Die cast aluminium alloy 380
Pressure actuator	Piston
Height	6.37 in (161.80 mm)
Depth	3.11 in (78.99 mm)
Width	3.5 in (88.9 mm)
Operating position	Any position
Materials in contact with fluid	440 stainless steel Nitrile (Buna-N)
Short-circuit protection	10 A cartridge overload and short-circuit protection gL
Maximum operating rate	120 cyc/mn
Mechanical durability	3000000 cycles
Repeat accuracy	4 %
Net Weight	3 lb(US) (1.4 kg)

Environment

Vibration resistance	2 gn 40...150 Hz)IEC 68-2-6
Shock resistance	50 gn IEC 58-2-27
Standards	UL 508 CSA C22.2 No 14 CE
Product Certifications	UL Listed[RETURN]UL listed Marine[RETURN]CSA LR25490 class 3211 03
NEMA degree of protection	NEMA 4/4X/13 UL 50
Ambient Air Temperature for Operation	-23...85 °C (-10...185 °F)

Ordering and shipping details

Category	US1CP7G21522
Discount Schedule	CP7G
GTIN	785901721499
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.13 in (61.29 cm)
Package 1 Width	9.50 in (24.13 cm)
Package 1 Length	61.29 in (155.677 cm)
Package 1 Weight	3.0005 lb(US) (1.361 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

Contractual warranty

Warranty	18 months
----------	-----------