



Main

Product Type	Panel
Marketing Trade Name	QO
Rated Current	30 A
Number of Spaces	6
Max Short Circuit Current Rating	25 kA
Number of Phases	1 phase
Voltage Rating	120/240 V AC

Complementary

Wire Size	AWG 14...AWG 12 copper or aluminium
Circuit Breaker Type	QO
Phase Connection	BC

Environment

Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
---------------------------------------	---------------------------------

Ordering and shipping details

Category	01078-DE2 MISC
Discount Schedule	DE2
GTIN	785901650065
Nbr. of units in pkg.	1
Package weight(Lbs)	16.00 oz (453.592 g)
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.88 in (14.923 cm)
Package 1 width	5.25 in (13.335 cm)
Package 1 Length	10.75 in (27.305 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------