

Product data sheet

Characteristics

QO320ML1RB

Load center, QO, 3 phase, 20 spaces, 20 circuits, 125A convertible main lugs, NEMA3R, CSA, UL



Main

Marketing Trade Name	QO
Product Type	Load Center
Enclosure Type	Weatherproof enclosure
Cover Type	Surface cover

Complementary

Tightening Torque	Main lugs 50 lb.in, AWG 4...AWG 2/0, aluminium/copper
Load Center Type	Main lugs
Rated Current	125 A
Number of Spaces	20
Maximum Number of Single Pole Circuits	40
Number of Phases	3 phase
Ground Bar	Grounding bar (ordered separately)
Electrical Connection	Lugs
Wiring Configuration	4-wire
Enclosure Material	Welded galvanized steel
Height	22.70 in (576.58 mm)
Width	14.72 in (373.89 mm)
Depth	4.54 in (115.32 mm)

Environment

Enclosure Rating	NEMA 3R outdoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	cULus

Ordering and shipping details

Category	00158-CANADIAN 3-PH LOAD CENTERS
Discount Schedule	DE3
GTIN	785901751083
Nbr. of units in pkg.	1
Package weight(Lbs)	25.12 lb(US) (11.394 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.10 in (12.954 cm)
Package 1 width	15.40 in (39.116 cm)
Package 1 Length	23.70 in (60.198 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------