



SKU: AU-350-N

UPC: 0783669005752

Features & Benefits:

Description: Aluminum Mechanical Lug, Conductor Range 350-6, 2 Ports, 6 Holes, 1/2in Bolt Size, 1-3/4in Hole Spacing, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	2
Number of Mounting Holes	6
Number of Poles	1
Number of Ports / Wireways	2

Dimensions

Dimension G (IN)	0.625
Dimension G (mm)	15.875
Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	1.5
Height BX (IN)	3.75
Length (IN)	5.5
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.562
Mounting Hole Diameter (mm)	14.2748
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Tang Length (IN)	3.25
Tang Length (mm)	82.55
Tang Thickness (IN)	0.375
Tang Thickness (mm)	9.525
Tang Width (IN)	2.75
Tang Width (mm)	69.85
Weight (LB)	1.006
Weight BX (LB)	3.2131
Width (IN)	2.75
Width BX (IN)	6

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum

Voltage

Voltage Rating

35 kV