

XMLP016BC21FQ

Electronic pressure sensors, Pressure sensors
XM, transmitter, XMLP, 16 bar, G1/4 A male,
4...20 mA, DIN, set of 25



Main

Range of Product	Telemecanique Pressure sensors XM
Product or Component Type	Electronic pressure sensors
Pressure sensor type	Pressure transmitter
Pressure sensor name	XMLP
Electrical circuit type	Control circuit
Pressure Rating	232.06 psi (16 bar)
Local display	Without
Controlled fluid	Air -22...275 °F (-30...135 °C)) Fresh water 32...275 °F (0...135 °C)) Hydraulic oil -22...275 °F (-30...135 °C)) Gas -22...275 °F (-30...135 °C)) Refrigeration fluid -22...275 °F (-30...135 °C))
Fluid connection type	G 1/4A (male) DIN 3852-E
Electrical connection	1 male connector EN 175301-803-A (ex DIN43650) 3 pins
[Us] rated supply voltage	12...24 V DC SELV 7...33 V)
Current consumption	< 23 mA
Type of output signal	Analogue
Analogue output function	4...20 mA, 2-wire
Quantity per Set	Set of 25
Type of Packing	Group

Complementary

Pressure setting range	0.000000000...232.06 psi (0...16 bar)
Maximum permissible accidental pressure	696.2 psi (48 bar)
Destruction pressure	1392.4 psi (96 bar)
Materials in contact with fluid	Stainless steel AISI 316L Fluorocarbon FPM
Operating position	Any position
Protection Type	Load short-circuit Reverse polarity
Electromagnetic compatibility	Electrostatic discharge immunity test IEC 61000-4-2 8 kV air, 4 kV contact 1.2/50 µs shock waves immunity test IEC 61000-4-5 1 kV 42 Ohm Immunity to magnetic fields IEC 61000-4-8 100 A/m 50 Hz Electrical fast transient/burst immunity test IEC 61000-4-4 4 kV Susceptibility to electromagnetic fields IEC 61000-4-3 10 V/m 80...3000 MHz Radiated RF fields IEC 61000-4-6 10 V 0.01...80 MHz
[Uimp] rated impulse withstand voltage	0.5 kV
Response time on output	<= 2 ms 10...90 % of full scale
Measurement accuracy	+/- 0.5 % of the measuring range
Resolution	0.1 % of the measuring range
Drift of the sensitivity	+/- 0.02 % of measuring range/°K
Drift of the zero point	+/- 0.02 % of measuring range/°K
Mechanical durability	10000000 cycles
Net Weight	0.234 lb(US) (0.106 kg)

Diameter	1.02 in (26 mm)
Length	2.4 in (60.6 mm)

Environment

Standards	NSF ANSI 61 IEC 61326-2-3
Product Certifications	RCM[RETURN]CE[RETURN]cULus
Protective treatment	TC
Ambient Air Temperature for Operation	-22...185 °F (-30...85 °C)
Ambient Air Temperature for Storage	-58...212 °F (-50...100 °C)
Vibration resistance	20 gn 15...2000 Hz) IEC 60068-2-6
Shock resistance	100 gn 11 ms IEC 60068-2-27
IP degree of protection	IP65 conforming to IEC 60529

Ordering and shipping details

Category	US10DS222419
Discount Schedule	0DS2
GTIN	3389119638838
Returnability	No
Country of origin	CH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.34 in (3.400 cm)
Package 1 Width	1.34 in (3.400 cm)
Package 1 Length	3.39 in (8.600 cm)
Package 1 Weight	3.245 oz (92.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	25
Package 2 Height	5.24 in (13.300 cm)
Package 2 Width	7.48 in (19.000 cm)
Package 2 Length	7.64 in (19.400 cm)
Package 2 Weight	5.529 lb(US) (2.508 kg)
Unit Type of Package 3	S02
Number of Units in Package 3	50
Package 3 Height	5.91 in (15 cm)
Package 3 Width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)
Package 3 Weight	11.724 lb(US) (5.318 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations