



Main

Range	Masterpact
Device short name	MCH
Product or Component Type	Motor mechanism
Device Application	Control
Range compatibility	MasterPact MTZ2 MasterPact MTZ3

Complementary

Control Type	Standard
[Uc] control circuit voltage	200...250 V DC
Threshold tripping voltage	0.85...1.1 Un
Maximum power consumption in VA	180 VA
Overcurrent protection	2...3 x In 0.1 s
Maximum charging time	4 s
Maximum operating frequency	<= 3 cycles per minute
Provided contact	Limit switch contact 240 V 10 A

Environment

Provided equipment	1 instruction sheet
Offer type	Spare part

Ordering and shipping details

Category	01257-MASTERPACT MTZ ACCESS
Discount Schedule	DE2F
GTIN	3606481187116
Nbr. of units in pkg.	1
Package weight(Lbs)	4.31 lb(US) (1.957 kg)
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	4.92 in (12.5 cm)
Package 1 width	5.16 in (13.1 cm)
Package 1 Length	9.02 in (22.9 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Weight	26.21 lb(US) (11.887 kg)
Package 2 Height	11.81 in (30.0 cm)
Package 2 width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information